

INDEX

- 3D graphics 322
- accelerators 1
- adders 147
- arithmetic and logic unit (ALU) 171
- bandwidth 235
- binary floating-point 190
- bus width 237
- cache 89, 237
- cache line 245
- cache miss 237
- CEC 236
- central electronic complex 236
- checkpoint 226
- clock 57
- clock frequency 61
- clock jitter 60
- clock skew 60
- clocked storage elements 57
- computer arithmetic 148
- computer system 236
- CPI 4
- derived clocking 302
- dielectric loss 298
- digital appliance 311
- digital circuits 31
- DRAM 275
- DSP cores 1
- embedded DRAM 278
- embedded system 311
- end around carry adder 199
- energy-delay space 32
- error correction 216
- error detection 215
- finite cache effect 240
- flip-flop 63
- floating-point unit 313
- forwarded clocking 302
- FR-4 296
- fused multiply-add 190
- gated-clock 4
- latch 61
- leading zero anticipation 190
- leakage 2
- leakage current 324
- line size 247
- low power 311
- low-voltage SRAM 100
- mesochronous 304
- microcontrollers 1
- microprocessor 209
- miss penalty 241
- miss rate 237
- miss ratio 261
- multicore 16
- multithread 238
- optics 237
- parallel data bus 290
- pipeline 4, 57, 314
- placement 123
- plesiochronous 305
- power 57
- power-switch 329
- prefetching 252
- processor core 311
- queuing 251
- reconfigurable 4
- redundancy 213
- register file 97
- semi-dynamic design 179
- six-transistor SRAM cell 109
- skin effect 298
- source synchronous 306
- SRAM 90, 326
- static memory 115
- system-on-a-chip (SOC) 325

- trailing edge 244
- trailing edge effect 246
- transistor sizing 32

- ultra-low-power 27

- virtualization 275
- voltage-mode sense amplifiers 96

- wavelength division multiplexing 283
- WDM 283