

IEEE TRANSACTIONS ON POWER ELECTRONICS

A PUBLICATION OF THE IEEE POWER ELECTRONICS SOCIETY



JUNE 2019

VOLUME 34

NUMBER 6

ITPEE8

(ISSN 0885-8993)

LETTERS

| | | |
|---|---|------|
| Current-Collapse-Free and Fast Reverse Recovery Performance in Vertical GaN-on-GaN Schottky Barrier Diode | <i>S. Han, S. Yang, R. Li, X. Wu, and K. Sheng</i> | 5012 |
| Integrated Driving/Charging/Discharging Battery-Powered Four-Phase Switched Reluctance Motor Drive With Two Current Sensors | <i>H.-C. Chen, W.-A. Wang, and B.-W. Huang</i> | 5019 |
| Optimal Charging of Nonlinear Capacitors | <i>Y. Perrin, A. Galisultanov, H. Fanet, and G. Pillonnet</i> | 5023 |
| Automated Heatsink Optimization for Air-Cooled Power Semiconductor Modules | <i>T. Wu, Z. Wang, B. Ozpineci, M. Chinthavali, and S. Campbell</i> | 5027 |
| Wide Load Range ZVZCS Three-Level DC–DC Converter With Compact Structure | <i>Y. Shi, X. Wang, J. Xi, X. Gui, and X. Yang</i> | 5032 |
| A Multi-Mode Flexible Power Point Tracking Algorithm for Photovoltaic Power Plants | <i>H. D. Tafti, C. D. Townsend, G. Konstantinou, and J. Pou</i> | 5038 |
| Exact Solution of ZVS Boundaries and AC-Port Currents in Dual Active Bridge Type DC–DC Converters | <i>S. S. Shah, V. M. Iyer, and S. Bhattacharya</i> | 5043 |

PAPERS

Highlighted Papers

| | | |
|---|--|------|
| Switched Tank Converters | <i>S. Jiang, S. Saggini, C. Nan, X. Li, C. Chung, and M. Yazdani</i> | 5048 |
| PowerSynth: A Power Module Layout Generation Tool | <i>T. M. Evans, Q. Le, S. Mukherjee, I. A. Razi, T. Vrotsos, Y. Peng, and H. A. Mantooth</i> | 5063 |

Papers with Active Content

| | | |
|---|---|------|
| Realization of 24-Sector SVPWM With New Switching Pattern for Six-Phase Induction Motor Drive | <i>S. M. Suhel and R. Maurya</i> | 5079 |
| Dynamic Capabilities of Multi-MHz Inductive Power Transfer Systems Demonstrated With Batteryless Drones | <i>J. M. Arteaga, S. Aldhafer, G. Kkelis, C. Kwan, D. C. Yates, and P. D. Mitcheson</i> | 5093 |

(Contents Continued on Page 5009)

| | | |
|---|--|------|
| Micro-Energy Harvesting System Including a PMU and a Solar Cell on the Same Substrate With Cold Startup From 2.38 nW and Input Power Range up to 10 μ W Using Continuous MPPT | <i>E. Ferro, V. M. Brea, P. López, and D. Cabello</i> | 5105 |
| <i>High-Power Converters</i> | | |
| Decentralized Control Method for Modular Multilevel Converters | <i>B. Xia, Y. Li, Z. Li, G. Konstantinou, F. Xu, F. Gao, and P. Wang</i> | 5117 |
| Novel Hybrid DC/DC Converter Topology for HVDC Interconnections | <i>B. Li, X. Zhao, D. Cheng, S. Zhang, and D. Xu</i> | 5131 |
| Asymmetrical Reactive Power Capability of Modular Multilevel Cascade Converter Based STATCOMs for Offshore Wind Farm | <i>T. Tanaka, K. Ma, H. Wang, and F. Blaabjerg</i> | 5147 |
| Autotuning Control System by Variation of Self-Inductance for Dynamic Wireless EV Charging With Small Air Gap | <i>S. Y. Jeong, J. H. Park, G. P. Hong, and C. T. Rim</i> | 5165 |
| 20-kW Zero-Voltage-Switching SiC-MOSFET Grid Inverter With 300 kHz Switching Frequency | <i>N. He, M. Chen, J. Wu, N. Zhu, and D. Xu</i> | 5175 |
| Design and Control of Unidirectional DC–DC Modular Multilevel Converter for Offshore DC Collection Point: Theoretical Analysis and Experimental Validation | <i>H. Liu, M. S. A. Dahidah, J. Yu, R. T. Naayagi, and M. Armstrong</i> | 5191 |
| Improved Three Switch-Active Clamp Forward Converter With Low Switching and Conduction Losses | <i>C.-E. Kim, J. Baek, and J.-B. Lee</i> | 5209 |
| Modelling a Multilevel LCC Resonant AC-DC Converter for Wide Variations in the Input and the Load | <i>J. A. Martín-Ramos, Ó. Pardo-Vaquero, J. Díaz, F. Nuño, P. J. Villegas, and A. Martín-Pernía</i> | 5217 |
| Investigation of a Non-isolated Reduced Redundant Power Processing DC/DC Converter for High-Power High Step-Up Applications | <i>C. G. Zogogianni, E. C. Tatakis, and V. Porobic</i> | 5229 |
| Energy Storage Requirement Reduction Using Negative-Voltage States of a Full-Bridge Modular Multilevel Converter | <i>Q. Song, W. Yang, B. Zhao, S. Xu, H. Rao, and Z. Zhu</i> | 5243 |
| Design Considerations and Development of an Innovative Gate Driver for Medium-Voltage Power Devices With High dv/dt | <i>A. Anurag, S. Acharya, Y. Prabowo, G. Gohil, and S. Bhattacharya</i> | 5256 |
| Particle Swarm Optimization-Based Parameter Design Method for S/CLC-Compensated IPT Systems Featuring High Tolerance to Misalignment and Load Variation | <i>Y. Yao, Y. Wang, X. Liu, Y. Pei, D. Xu, and X. Liu</i> | 5268 |
| A New Standby Structure Integrated With Boost PFC Converter for Server Power Supply | <i>J. Baek, J.-K. Kim, J.-B. Lee, M.-H. Park, and G.-W. Moon</i> | 5283 |
| <i>Power Quality and Utilities</i> | | |
| Control Strategy for Arc-Suppression-Coil-Grounded Star-Connected Power Electronic Transformers | <i>S. Ouyang, J. Liu, Y. Yang, X. Chen, S. Song, and H. Wu</i> | 5294 |
| Use of Integrated Photovoltaic-Electric Spring System as a Power Balancer in Power Distribution Networks | <i>T. Yang, K.-T. Mok, S.-S. Ho, S.-C. Tan, C.-K. Lee, and R. S. Y. Hui</i> | 5312 |
| A Control Algorithm Based on the Conservative Power Theory for Cooperative Sharing of Imbalances in Four-Wire Systems | <i>C. Burgos-Mellado, R. Cárdenas, D. Sáez, A. Costabeber, and M. Sumner</i> | 5325 |
| <i>EMI/EMC</i> | | |
| Investigation of Magnetic Field Immunity and Near Magnetic Field Reduction for the Inductors in High Power Density Design | <i>Y. Lai, S. Wang, and B. Zhang</i> | 5340 |
| An Improved H8 Topology for Common-Mode Voltage Reduction | <i>Y. Xiang, X. Pei, M. Wang, P. Shi, and Y. Kang</i> | 5352 |
| Flyback PFC With a Series-Pass Module in Cascode Structure for Input Current Shaping | <i>C.-P. Tung, K.-W. Wang, K.-W. Ho, J. P.-W. Chow, J. W.-T. Fan, W.-T. Chan, and H. S.-H. Chung</i> | 5362 |
| <i>Renewable Energy</i> | | |
| Further Study on a PWM Current-Source-Converter-Based Wind Energy Conversion System Considering the DC-Link Voltage | <i>Q. Wei, B. Wu, D. Xu, and N. R. Zargari</i> | 5378 |
| Analysis and Dynamic Control of a Dual-Stator BDFIG-DC System Supplying DC Grid With Minimized Torque Ripple Through Harmonic Current Injection | <i>Y. Jiang, M. Cheng, P. Han, Q. Wang, and X. Wang</i> | 5388 |
| Reduced-Sensor-Based PV Array-Fed Direct Torque Control Induction Motor Drive for Water Pumping | <i>S. Shukla and B. Singh</i> | 5400 |
| A Generalized Droop Control for Grid-Supporting Inverter Based on Comparison Between Traditional Droop Control and Virtual Synchronous Generator Control | <i>X. Meng, J. Liu, and Z. Liu</i> | 5416 |

| | |
|--|------|
| A Modulation Method for Leakage Current Reduction in a Three-Phase Grid-Tie Quasi-Z-Source Inverter | 5439 |
| <i>N. Noroozi, M. Yaghoubi, and M. R. Zolghadri</i> | |
| An Adaptive Control Scheme for Flexible Power Point Tracking in Photovoltaic Systems | 5451 |
| <i>H. D. Tafti, A. Sangwongwanich, Y. Yang, J. Pou, G. Konstantinou, and F. Blaabjerg</i> | |
| <i>Low-Power Converters</i> | |
| Design and Analysis of a Developed Multiport High Step-Up DC-DC Converter With Reduced Device Count and Normalized Peak Inverse Voltage on the Switches/Diodes | 5464 |
| <i>K. Varesi, S. H. Hosseini, M. Sabahi, E. Babaei, S. Saeidabadi, and N. Vosoughi</i> | |
| Multimode Control Strategy for SiC MOSFETs Based Semi-Dual Active Bridge DC-DC Converter | 5476 |
| <i>D. Sha, J. Zhang, and T. Sun</i> | |
| High Step-Up Y-Source Inverter With Reduced DC-Link Voltage Spikes | 5487 |
| <i>H. Liu, Z. Zhou, K. Liu, P. C. Loh, W. Wang, D. Xu, and F. Blaabjerg</i> | |
| A New Analytical Model for Predicting dv/dt -Induced Low-Side MOSFET False Turn-ON in Synchronous Buck Converters | 5500 |
| <i>R. Li, Q. Zhu, and M. Xie</i> | |
| Resonant Analysis of Magnetic Coupling Wireless Power Transfer Systems | 5513 |
| <i>Z.-J. Liao, Y. Sun, Z.-H. Ye, C.-S. Tang, and P.-Y. Wang</i> | |
| Minimum Active Switch Requirements for Single-Phase PFC Rectifiers Without Electrolytic Capacitors | 5524 |
| <i>S. Li, W. Qi, J. Wu, S.-C. Tan, and S.-Y. Hui</i> | |
| An Adaptive Variable-Frequency Control With Constant Crossover Frequency Achieving Fast Transient Response for Wide-Operation-Range Flyback Converter | 5537 |
| <i>C.-H. Cheng, C.-J. Chen, and S.-S. Wang</i> | |
| Output-Series Connected Dual Active Bridge Converters for Zero-Voltage Switching Throughout Full Load Range by Employing Auxiliary LC Networks | 5549 |
| <i>Z. Guo, D. Sha, and K. Song</i> | |
| A Negative-Output High Quadratic Conversion Ratio DC-DC Converter With Dual Working Modes | 5563 |
| <i>J. Li and J. Liu</i> | |
| <i>Integrated Packaging</i> | |
| Flexible PCB-Based 3-D Integrated SiC Half-Bridge Power Module With Three-Sided Cooling Using Ultralow Inductive Hybrid Packaging Structure | 5579 |
| <i>C. Chen, Z. Huang, L. Chen, Y. Tan, Y. Kang, and F. Luo</i> | |
| <i>Power Electronic Drives</i> | |
| A Commutation Torque Ripple Suppression Strategy for Brushless DC Motor Based on Diode-Assisted Buck-Boost Inverter | 5594 |
| <i>Y. Cao, T. Shi, X. Li, W. Chen, and C. Xia</i> | |
| Dual-Segment Three-Phase PMSM With Dual Inverters for Leakage Current and Common-Mode EMI Reduction | 5606 |
| <i>Z. Shen, D. Jiang, T. Zou, and R. Qu</i> | |
| Effects of Stator Iron Loss and Current-Loop Delay on Copper-Loss-Minimizing Torque Control of BLDCM: Analysis and Improvements | 5620 |
| <i>H. Zhang, M. Dou, and L. Yan</i> | |
| A Hybrid Solenoid Coupler for Wireless Charging Applications | 5632 |
| <i>A. Tejada, S. Kim, F. Y. Lin, G. A. Covic, and J. T. Boys</i> | |
| Estimation Method of Stator Winding Resistance for Induction Motor Drives Based on DC-Signal Injection Suitable for Low Inertia | 5646 |
| <i>F. Baneira, L. Asiminoaei, J. Doval-Gandoy, H. A. M. Delpino, A. G. Yepes, and J. Godbersen</i> | |
| Investigation of a Four-Switch Four-Leg Inverter: Modulation, Control, and Application to an IPMSM Drive | 5655 |
| <i>W. Li, S. Xuan, Q. Gao, and L. Luo</i> | |
| Hybrid RPWM Technique Based on Modified SVPWM to Reduce the PWM Acoustic Noise | 5667 |
| <i>Y. Huang, Y. Xu, W. Zhang, and J. Zou</i> | |
| Load Torque and Moment of Inertia Identification for Permanent Magnet Synchronous Motor Drives Based on Sliding Mode Observer | 5675 |
| <i>C. Lian, F. Xiao, S. Gao, and J. Liu</i> | |
| Performance of a Loss Model Based Nonlinear Controller for IPMSM Drive Incorporating Parameter Uncertainties | 5684 |
| <i>M. N. Uddin, M. M. Rahman, B. Patel, and B. Venkatesh</i> | |
| <i>Passive Components and Materials</i> | |
| A Practical Approach for Core Loss Estimation of a High-Current Gapped Inductor in PWM Converters With a User-Friendly Loss Map | 5697 |
| <i>J. Wang, K. J. Dagan, X. Yuan, W. Wang, and P. H. Mellor</i> | |
| <i>Lighting Applications</i> | |
| On Supplying LEDs From Very Low DC Voltages With High-Frequency AC-LED Drivers | 5711 |
| <i>I. Castro, A. Vazquez, D. G. Aller, M. Arias, D. G. Lamar, and J. Sebastián</i> | |
| <i>Discrete and Integrated Semiconductors</i> | |
| Piecewise Analytical Transient Model for Power Switching Device Commutation Unit | 5720 |
| <i>B. Shi, Z. Zhao, and Y. Zhu</i> | |

| | | |
|---|---|------|
| A Novel Non-Intrusive Technique for BTI Characterization in SiC MOSFETS | <i>J. A. O. González and O. Alatise</i> | 5737 |
| <i>Diagnostics in Power Electronics</i> | | |
| A Noninvasive Online Monitoring Method of Output Capacitor's <i>C</i> and ESR for DCM Flyback Converter | <i>K. Yao, H. Li, L. Li, C. Guan, L. Li, Z. Zhang, and J. Chen</i> | 5748 |
| Open-Circuit Fault Diagnosis and Tolerance Strategy Applied to Four-Wire T-Type Converter Systems | <i>K. Wang, Y. Tang, and C.-J. Zhang</i> | 5764 |
| A Simple Analytical Model of Capacity Fading for Lithium–Sulfur Cells | <i>V. Sedlakova, J. Sikula, P. Sedlak, O. Cech, and L. Urrutia</i> | 5779 |
| Fast Fault Protection Based on Direction of Fault Current for the High-Surety Power-Supply System | <i>H. Li, M. Chen, B. Yang, F. Blaabjerg, and D. Xu</i> | 5787 |
| <i>Control in Power Electronics</i> | | |
| Damping Low-Frequency Oscillations Through VSC-HVdc Stations Operated as Virtual Synchronous Machines | <i>L. Huang, H. Xin, and Z. Wang</i> | 5803 |
| An Enhanced DC-Bus Voltage-Control Loop for Single-Phase Grid-Connected DC/AC Converters | <i>S. Taghizadeh, M. J. Hossain, J. Lu, and M. Karimi-Ghartemani</i> | 5819 |
| A Novel Dynamic Ramp Valley Control in a Current-Mode Adaptive On-Time Controller for the On-Chip Buck Converter | <i>W.-W. Chen and J.-S. Lai</i> | 5830 |
| Robust Stability Analysis of <i>LCL</i> Filter Based Synchronverter Under Different Grid Conditions | <i>R. Rosso, J. Cassoli, G. Buticchi, S. Engelken, and M. Liserre</i> | 5842 |
| Source-Side Series-Virtual-Impedance Control to Improve the Cascaded System Stability and the Dynamic Performance of Its Source Converter | <i>X. Zhang, Q.-C. Zhong, V. Kadiramanathan, J. He, and J. Huang</i> | 5854 |
| Modeling Dual Active Bridge Converters in DC Distribution Systems | <i>J. A. Mueller and J. W. Kimball</i> | 5867 |
| Sensorless BLDC Motor Commutation Point Detection and Phase Deviation Correction Method | <i>X. Zhou, Y. Zhou, C. Peng, F. Zeng, and X. Song</i> | 5880 |
| Improved Pulse Density Modulation for Semi-bridgeless Active Rectifier in Inductive Power Transfer System | <i>M. Fan, L. Shi, Z. Yin, L. Jiang, and F. Zhang</i> | 5893 |
| On Nonlinear Control of Single-Phase Converters With Active Power Decoupling Function | <i>H. Yuan, S. Li, W. Qi, S.-C. Tan, and S.-Y. Hui</i> | 5903 |
| Power Control of Virtual Oscillator Controlled Inverters in Grid-Connected Mode | <i>D. Raisz, T. T. Thai, and A. Monti</i> | 5916 |
| Circuit-Parameter-Based Audiosusceptibility Model for Series Resonant Converter | <i>S. Joshi T. G. and V. John</i> | 5927 |
| The Dual-Current Control Strategy of Grid-Connected Inverter With <i>LCL</i> Filter | <i>Y. Guan, Y. Wang, Y. Xie, Y. Liang, A. Lin, and X. Wang</i> | 5940 |
| DAVIC: A New Distributed Adaptive Virtual Impedance Control for Parallel-Connected Voltage Source Inverters in Modular UPS System | <i>B. Wei, A. Marzàbal, R. Ruiz, J. M. Guerrero, and J. C. Vasquez</i> | 5953 |
| Observer-Based Predictive Vector-Resonant Current Control of Permanent Magnet Synchronous Machines | <i>Z. Song and F. Zhou</i> | 5969 |
| Neural Inverse Optimal Control Implementation for Induction Motors via Rapid Control Prototyping | <i>E. Quintero-Manriquez, E. N. Sanchez, R. G. Harley, S. Li, and R. A. Felix</i> | 5981 |
