

# Deep Learning for Logo Detection: A Survey

Sujuan Hou, *Member, IEEE*, Jiacheng Li, Weiqing Min, *Senior Member, IEEE*, Qiang Hou, Yanna Zhao, *Member, IEEE*, Yuanjie Zheng, *Member, IEEE*, and Shuqiang Jiang, *Senior Member, IEEE*

**Abstract**—When logos are increasingly created, logo detection has gradually become a research hotspot across many domains and tasks. Recent advances in this area are dominated by deep learning-based solutions, where many datasets, learning strategies, network architectures, etc. have been employed. This paper reviews the advance in applying deep learning techniques to logo detection. Firstly, we discuss a comprehensive account of public datasets designed to facilitate performance evaluation of logo detection algorithms, which tend to be more diverse, more challenging, and more reflective of real life. Next, we perform an in-depth analysis of the existing logo detection strategies and the strengths and weaknesses of each learning strategy. Subsequently, we summarize the applications of logo detection in various fields, from intelligent transportation and brand monitoring to copyright and trademark compliance. Finally, we analyze the potential challenges and present the future directions for the development of logo detection to complete this survey.

**Index Terms**—logo detection, computer vision, deep learning, datasets

## I. INTRODUCTION

Logos usually consist of texts, shapes, images, or their combination. Logo detection benefits a wide range of applications in different areas, such as intelligent transportation [1, 2], social media monitoring [3], and infringement detection [4, 5]. Meanwhile, some competitions have emerged, such as Robust Logo Detection Grand Challenge [5–8] and Few-shot Logo Detection [9].

The main task of logo detection is to determine the location of a specific logo in images/videos and identify them. Although it may be regarded as a particular object task, logo detection in real-world images can be pretty challenging since numerous brands may have highly diverse contexts, varied scales, changes in illumination, size, resolution, and even non-rigid deformation (as shown in Fig. 1).

Many previous works on logo detection employ hand-crafted features (like SIFT [10]) to represent logos and use statistical classifiers for classification. Such methods suffer from complex image preprocessing pipelines and poor robustness when dealing with a much larger number of logos. Recent years have witnessed the rousing success of deep learning since ImageNet Large Scale Visual Recognition Challenge

This work was supported by the National Nature Science Foundation of China (No.62072289, 61972378, U193620), CAAI-Huawei MindSpore Open Fund. S. Hou, J. Li, Q. Hou, Y. Zhao and Y. Zheng are School of Information Science and Engineering, Shandong Normal University, Shandong, 250358, China. Email: sujuanhou@sdu.edu.cn, 2021317140@stu.sdu.edu.cn, 2019309052@stu.sdu.edu.cn, yannazhao@sdu.edu.cn, and zhengyuanjie@gmail.com. W. Min and S. Jiang are with the Key Laboratory of Intelligent Information Processing, Institute of Computing Technology, Chinese Academy of Sciences, Beijing, 100190, China, and also with University of Chinese Academy of Sciences, Beijing, 100049, China. Email: minweiqing@ict.ac.cn, and sqjiang@ict.ac.cn.



Fig. 1: Examples of images in adverse conditions.

(ILSVRC) [11]. Deep learning-based solutions with expressive feature representation capability offer better robustness, accuracy, and speed and thus attract increasing attention. There are more than 100 papers about logo detection from 1993 to 2022, and a concise milestone of logo detection is shown in Fig. 2. We can see that many deep learning-based logo detection strategies have been proposed since 2015. This survey mainly concentrates on deep learning-based solutions specially developed for logo detection.

Even though deep learning has dominated the logo research community, a comprehensive and in-depth survey on deep learning-based solutions is lacking. In this survey, we mainly focus on the advances in recent deep learning for logo detection. We provide in-depth analysis and discussion on existing studies in various aspects, covering datasets, pipelined used, task types, detection strategies, loss functions, their contributions and limitations. We also try to analyze potential research challenges and future research directions for logo detection. We hope our work could provide a novel perspective to promote the understanding of deep learning-based logo detection, foster research on open challenges, and speed up the development of the logo research field.

The rest of this paper is organized as follows. In Section II, we investigate the public logo detection datasets. In Section III, we review and organize the currently available work on logo detection. In Section IV, we introduce the applications of logo detection in real-world scenarios. In Section V, we discuss its challenges and prominent future research directions. Finally, we summarize the whole text in Section VI.

## II. LOGO DATASETS

Deep learning has brought great success to object detection in recent years, where datasets play a crucial role. Datasets




Fig. 2: A concise milestone for logo detection.



Fig. 3: Logo images sampled from different datasets.

are not only a common basis for comparing and measuring the performance of algorithms but also an essential factor in supporting advanced object detection algorithms. This section provides an overview of the logo datasets for detection. In addition, we also give a brief summary of existing logo classification datasets.

In recent years, many logo datasets intended for detection have been created to solve the problem of large realistic datasets with accurate ground truth. The use of these datasets enables qualitative as well as quantitative comparisons and allows benchmarking of different algorithms. We conducted statistics on existing datasets commonly used for logo detection and classified them into three types based on their scale: small-scale, medium-scale, and large-scale. Table I provides statistics on the available logo datasets, and Fig. 3 gives some illustrative examples from these datasets.

The small-scale datasets include BelgaLogos [12], FlickrLogos-32 [13], etc. As the first benchmark dataset proposed for logo detection, BelgaLogos [12] consists of 10,000 images of natural scenes, with 37 different logos and 2,695 instances of logos labeled with bounding boxes. FlickrLogos-32 [13], one of the most popular small-scale datasets for logo detection, comprises 32 different classes with 70 images in each class. The images in this dataset are mainly captured from the real world, and many contain

occlusions, appearance changes, and lighting changes, making detecting this dataset very challenging.

Datasets with medium-scale include Logo-Net [14], QMUL-OpenLogo [15], FoodLogoDet-1500 [16], etc. Logo-Net [14] is built for detecting logos and identifying brands from real-world product images. It consists of two sub-datasets, namely Logo-18 and Logo-160. QMUL-OpenLogo [15] is an open benchmark for logo detection, constructed by aggregating seven existing datasets and building an open protocol for logo detection evaluation. The QMUL-OpenLogo dataset has a highly imbalanced distribution and significant variation in scale, which is critical to verify the performance of the detection algorithm. FoodLogoDet-1500 [16] is the first high-quality public dataset of food logos with uneven distribution among different food logo classes, which poses a challenge to the small sample food logo detection algorithms. The dataset is composed of 1,500 food logo classes with 99,768 images.

There are also some large-scale datasets, such as LogoDet-3K [17] and PL8K [18]. LogoDet-3K [17] divides all logos into nine super-classes based on the needs of daily life and the main positioning of common enterprises, namely Clothing, Food, Transportation, Electronics, Necessities, Leisure, Medicine, Sports, and Others. The dataset consists of 3,000 logo classes, 158,652 images, and 194,261 logo objects. The number of logo classes contained in different super-classes

TABLE I: Statistics of existing logo detection datasets.

#Scale	#Datasets	#Logos	#Brands	#Images	#Objects	#Public	#Year
Small	BelgaLogos [12]	37	37	10,000	2,695	Yes	2009
	FlickrLogos-27 [19]	27	27	1,080	4,671	Yes	2011
	FlickrLogos-32 [13]	32	32	2,240	5,644	Yes	2011
	MICC-Logos [10]	13	-	720	-	No	2013
	Logo-18 [14]	18	10	8,460	16,043	No	2015
	Logos-32plus [20]	32	32	7,830	12,302	No	2017
	Top-Logo-10 [21]	10	10	700	-	No	2017
	Video SportsLogo [22]	20	20	2,000	-	No	2017
	VLD 1.0 [23]	66	66	25,189	-	No	2019
	SportLogo [24]	31	31	2,836	-	Yes	2020
VLD-45 [25]	45	45	45,000	-	No	2020	
Medium	Logo-160 [14]	160	100	73,414	130,608	No	2015
	Logos-in-the-Wild [26]	871	871	11,054	32,850	Yes	2017
	QMUL-OpenLogo [15]	352	352	27,083	-	Yes	2018
	PL2K [27]	2,000	2,000	295,814	-	No	2019
	FoodLogoDet-1500 [16]	1,500	-	99,768	145,400	Yes	2021
Large	Open Brands [28]	1,216	559	1,437,812	3,113,828	No	2020
	LogoDet-3K [17]	3,000	2,864	158,652	194,261	Yes	2020
	PL8K [18]	7,888	7,888	3,017,146	-	No	2022

varies greatly. For example, the Food, Clothes, and Necessities contain more images and objects than other super-classes. The imbalanced distribution across different logo classes of LogoDet-3K poses a challenge to effectively detecting logos with few samples. PL8K [18] is a large logo detection dataset constructed semi-automatically. The dataset consists of 7,888 logo brands and 3,017,146 images, and at least 20 images per class.

In addition, there are also some datasets built for logo classification, e.g. WebLogo-2M [29] and Logo 2K+ [30]. Weblogo-2M [29] is obtained by automatic web data acquisition and processing. The dataset excludes images with small widths and/or heights and duplicate images. Compared with other datasets, the Weblogo-2M presents three unique properties inherent to large-scale data exploration for learning scalable logo models: (1) Weak Annotation. (2) Noisy (False Positives). (3) Class Imbalance. Logo-2K+ [30] is a large-scale high-quality logo dataset. It covers a variety of logo classes from the real world, and different types of logo images have various logo appearances, scales, and backgrounds since they are collected from different websites. The dataset has high spatial coverage of categories including Food, Clothes, Institutions, Accessories, Transportation, Electronics, Necessities, Cosmetics, Leisure, and Medical. The number of images is imbalanced among different categories. For instance, Food has 769 logo classes, while Medical has only 48.

As with common object detection, mAP [31] is the most commonly used evaluation metric to measure logo detectors.

### III. LOGO DETECTION

In logo detection, logo classification is also an essential part. Therefore, we briefly summarize logo classification before introducing logo detection.

#### A. Logo Classification

As one of the most critical tasks in computer vision, logo classification aims to recognize the logo name corresponding to the input image. According to different feature extraction strategies, existing classification methods are divided into two

categories: *traditional machine learning-based methods* and *deep learning-based methods*. Some representative methods will be described briefly in the following.

1) *Traditional Machine Learning-based Methods*: The traditional logo classification methods extract features through manual features, such as SIFT and HOG, and then classify them by a classifier. Support Vector Machine (SVM) [32] is a classifier that performs binary data classification in a supervised learning manner. In traditional logo classification, SVM also shows excellent performance [33–36]. Carvalho *et al.* [35] proposed a self-learning and automatic detection method that performs detection without any prior data. The scheme automatically identifies the candidate regions of the localization logo, uses the HOG features extracted from the localization to train the object detector and some sub-detectors and uses the SVM to recognize the logo image.

K-Nearest Neighbor (KNN) is a supervised learning algorithm commonly used in classification [37, 38]. Gopinathan *et al.* [38] proposed a vehicle logo recognition system in 2018. They used Euclidean distance on the initial training dataset to summarize the pixel intensity distribution by applying each channel’s mean and standard deviation and used the K-means algorithm to cluster the color histogram features to group different logos. Then HOG and KNN algorithms extract logo features and classify logos.

2) *Deep Learning-based Methods*: In recent years, with the continuous development of deep learning, deep learning based solutions have also been successfully applied to logo classification [39–46]. Karimi *et al.* [43] used the DCNN logo recognition algorithm, which conducted a pre-trained model for feature extraction and then used SVM for logo classification. They also used transfer learning to improve existing pre-trained models for logo recognition. Finally, the fine-tuned deep model is applied to the parallel structure to obtain a more efficient deep model for logo recognition.

The latest trend in logo classification is to design efficient networks with limited resources [18, 30, 47, 48]. Wang *et al.* [30] proposed a Discriminative Region Navigation and Augmentation Network (DRNA-Net), which is capable of discovering more informative regions and expanding these




Fig. 4: The architecture of DRNA-Net [30].

regions for logo classification. DRNA-Net is mainly divided into four parts: navigator sub-network, teacher sub-network, region-oriented data augmentation sub-network, and scrutinizer sub-network. Specifically, the navigation sub-network first computes the amount of information in all regions generated by pre-defined anchors in the image. In order to make the navigation sub-network selects the most informative logo-relevant regions, the teacher sub-network then evaluates each regions confidence that belongs to the ground-truth class. The region-oriented data augmentation sub-network can augment the selected regions to localize more relevant logo regions. Finally, the features of augment regions and the whole image are fused by the scrutinizer sub-network to obtain a unified feature representation for logo prediction. The architecture of DRNA-Net is shown in Fig. 4. In order to distinguish visually similar logos, Li *et al.* [18] proposed a multi-task learning architecture named SeeTek based on deep learning and scene text recognition. This model combines deep metric learning and text recognition into a single model leading to considerable performance improvements. The architecture of SeeTek is shown in Fig. 5.

## B. Logo Detection

Logo detection can be seen as a particular case of general object detection. The purpose of logo detection is to detect logo instances of predefined logo classes in images or videos [14]. In this section, we will present the current state-of-the-art work on logo detection in detail.

Before the development of deep learning, early approaches to logo detection were implemented based on hand-crafted visual features (e.g., SIFT and HOG) and traditional classification models (e.g., SVM) [49–52]. For example, Sahbi *et al.* [10] proposed a logo matching system in 2013, where they used SIFT to conduct logo detection and recognition. The designed system can not only recognize and match multiple reference logos in an image but also is suitable for detecting similar logos. However, such traditional logo detection methods have certain limitations: (1) The region-selective search algorithm based on sliding windows lacks

pertinence, especially with high time complexity. (2) The hand-designed features lack robustness to the variation of logo diversity.

In recent research, deep learning has emerged as the mainstream for logo detection. According to different learning strategies, we categorize these models into region-based Convolutional Neural Network models, YOLO-based models, Single Shot Detector-based models, Feature Pyramid Network-based models and other models.

1) *Region-based Convolutional Neural Network models (RCNNs)*: Region-based Convolutional Neural Network (R-CNN [53]) is a typical region proposals-based approach. Compared with traditional detection algorithms, R-CNN has achieved considerable performance improvement. However, R-CNN still has several shortcomings. For example, R-CNN uses the Selective Search (SS) [54] algorithm to generate many overlapping boxes for redundant computation, leading to slow detection speed and taking up a large amount of storage space. The later proposed **Fast R-CNN** [55] solves this issue by creating an end-to-end trainable system. However, Fast R-CNN still uses the SS algorithm to generate region proposals, limiting its speed. To solve this problem, Ren *et al.* proposed **Faster R-CNN** [56] in 2015, which adopts region proposal network (RPN) to generate region proposals. Although Faster R-CNN has advantages in speed and efficiency, it still suffers from computational redundancy and low efficiency of small object detection.

Recently, RCNN-based logo detection has also achieved considerable success [26, 57–59]. Since the same brand may contain multiple products, different product images of the same brand may present different visual content, and traditional image recognition methods cannot directly solve the problem of brand recognition. Hoi *et al.* [14] proposed a DeepLogo-DRCN scheme for logo detection and brand recognition by exploring several deep region-based convolutional network (DRCN) techniques for object detection. They adopt Selective Search [54] to generate regions of interests (RoIs) and input the RoIs into a fully convolutional network (FCN). Feature vectors are then obtained through fully connected layers (FCs) to train the final classifiers and bounding box




Fig. 5: The architecture of SeeTek [18].

regressors. The overall architecture is trained in an end-to-end way. This is the first work on deep learning-based logo detection, which provides a new perspective on logo detection research.

We know that training a large-scale logo detection model requires a large amount of data, and the logo datasets usually suffer from data scarcity. Data augmentation and transfer learning are common solutions to release the problem of data scarcity. Oliveira *et al.* [60] proposed an automatic graphic logo detection system based on Fast R-CNN [55], which is robust to unconstrained imaging conditions. They used transfer learning and data augmentation to train a convolutional neural network model and allowed multiple detections of potential regions containing objects. Experimental results demonstrate that this strategy is superior to the traditional methods [13]. However, the adopted SS algorithm still generates redundant calculations, reducing detection speed. In addition, Li *et al.* [61] built Faster R-CNN for logo detection by using transfer learning, data augmentation, and clustering to guarantee suitable hyperparameters and more precise anchors for RPN. The experimental results show that this improvement could significantly improve the detection accuracy.

2) *YOLO-based models (YOLOs)*: YOLOs are single-stage detectors that are commonly used for logo detection. YOLOs directly detect images and outputs the category and location information of the detected objects. Early YOLO [62] has fast detection speed, but at the expense of accuracy, especially for small objects. The later improvements, like YOLOv2 [63], YOLOv3 [64], YOLOv4 [65], YOLOF [66], YOLOR [67], YOLOX [68], YOLOv6 [69], YOLOv7[70] improve the overall performance of YOLO, balancing the accuracy and speed.

YOLOs are widely used in vehicle logo detection. Given that real-time and high efficiency is essential issues in vehicle logo detection. Inspired by the superiority of deep learning in feature extraction, Yin *et al.* [71] proposed a high-efficiency vehicle logo detection system based on YOLOv2 [63]. Compared with the traditional methods based on manual extraction

features, the system has the advantages of self-learning features and direct image input and can realize the dual functions of positioning and recognition of the vehicle logo. In the case of complex backgrounds, a vehicle logo usually occupies only a small part of the image. Therefore, it is challenging to identify vehicle logos in real-world scenarios accurately. To solve this issue, Yang *et al.* [72] proposed a data-driven enhanced training method based on YOLOv3 [64]. They combined a feature extraction network with a multi-scale decision scheme to improve the detection accuracy of vehicle logos. However, the detection results of vehicle logos in complex scenes are unsatisfactory. Based on [72], Zhang *et al.* [73] analyzed the characteristics of vehicle identification in static images and found that both the network for feature extraction and the training strategy for detection has a significant impact on the accuracy of vehicle identification. They proposed a lightweight network structure with separable convolutions to replace traditional methods to improve detection accuracy and speed under the YOLO-based framework. Experiments show that this method improves the real-time performance of vehicle logo detection and also improves the detection accuracy of small-scale objects while maintaining the speed to a certain extent.

In various fields, the frequency of different logos usually varies widely. Therefore, the number of different logo classes is often unbalanced, making it difficult for models to detect logo classes with small samples correctly. Wang *et al.* [17] proposed a robust baseline method Logo-Yolo based on YOLOv3 [64]. They first adopt the K-means clustering algorithm to select the number of candidate anchor boxes and aspect ratio dimensions. They then used Focal loss to address the imbalance of samples in the dataset. Lastly, they introduced CIoU loss to improve bounding box regression results. Compared with YOLOv3 [64], the performance of this method is significantly improved in predicting small objects and objects in complex backgrounds. However, in some specific cases, the method also shows poor performance,




Fig. 6: The architecture of MFDNet [16].

such as detecting similar or occluded logos.

3) *Single Shot Detector-based models (SSDs)*: Single Shot MultiBox Detector (SSD) [74] is another single-stage detector using a single deep neural network. SSD uses multi-scale feature maps to detect objects at different scales, with the bottom layer predicting small objects and the top layer predicting large objects. While ensuring the detection speed, the detection accuracy of SSD outperforms a comparable state-of-the-art Faster R-CNN model. Therefore, SSDs are also widely used in vehicle logo detection [58]. Previous works usually detect vehicle logos at the same scale without considering the multi-scale variation of vehicle logos. However, the vehicle logos captured by the camera are of various sizes. It is essential to design an algorithm with multi-scale vehicle logo detection ability. To this end, Zhang *et al.* [25] proposed a multi-scale vehicle logo detection (SVLD) based on SSD [74] to assist in the recognition of vehicles by modifying the pretraining strategy, adding a feature extraction layer, and controlling the ratio of positive and negative samples. According to the characteristics of the vehicle, a preset frame and parameter settings are designed to effectively reduce redundant calculations and accelerate the convergence of the model quickly. Compared with SSD, the detection accuracy of SVLD is improved, but the time complexity is slightly increased due to the addition of the feature extraction layer. In addition, although SSDs have competitive accuracy compared to other single-stage methods, they are still insufficient in detecting small objects.

4) *Feature Pyramid Network-based models (FPNs)*: Lin *et al.* proposed Feature Pyramid Networks (FPN) [75] in 2017, which mainly solves the multi-scale problem in object detection by changing the connectivity of the network. FPN dramatically improves the performance of small object detection without increasing the amount of calculation. In recent years, many works have adopted FPN to solve problems of logo detection, like multi-scale and small objects [16, 28, 76, 77] and these FPNs have achieved exciting results.

Aiming at the problems of multi-scale and other geometric variations of logos, Meng *et al.* [76] proposed obtaining sufficient features for logo (OSF-Logo) based on FPN. Specifically, they introduced the Regulated Deformable Convolution (RDC) module in a specific layer of FPN, which allows the sampling point positions of the convolution kernel at different positions to adaptively change according to the content, thereby adapting

to the geometric changes of the logo. Meanwhile, they adopt an up-sampling operator in FPN to generate an adaptive kernel that fully aggregates rich semantic information. Therefore, OSF-Logo can quickly perceive a wide range of content and effectively detect multi-scale logos. Similarly, Jin *et al.* [28] designed a network called Brand Net. Brand Net uses FPN to extract multi-scale features. On this basis, it introduces an anchor refinement network in FPN to remove negative anchors, thus greatly reducing the number of anchor boxes. Therefore, it can effectively detect logos with different scales and significantly improve the detection performance of small logos. Detection Transformers (DETR) [78] has problems detecting small objects, so it cannot be directly used for multi-scale logo detection. To solve this issue, Velazquez *et al.* [77] incorporated Feature Pyramid (FP) into DETR architecture. They firstly split the penultimate layer of the feature pyramid into four patches of the same size as the smallest feature map in the pyramid. They then fed these patches into the DETR pipeline for prediction. This method effectively detects small objects. However, the backward propagation computation of this method increases memory consumption. Recently, Hou *et al.* [16] proposed a multi-scale feature decoupling network (MFDNet) for logo detection to solve the problem of distinguishing multiple logo categories. MMFDNet comprises two components: Balanced Feature Pyramid (BFP) and Feature Offset Module (FOM). The former is designed to fuse multi-scale features using the same deep feature map to integrate balanced semantic features. At the same time, the latter comprises an automatically learned anchor region proposal network for pixel-level offsets to search for the best features for logos. The architecture of MFDNet is shown in Fig. 6.

5) *Other models*: Some other models used in logo detection are introduced in this section.

In order to solve the problem of limited logo data, Su *et al.* [15] proposed a data augmentation strategy focusing on logo context optimization: Contextual Adversarial Learning (CAL). CAL takes an image with a logo object as input and generates context-consistent synthetic images that can be used as additional training data. However, the distribution of this synthetic image is different from the actual test image. To solve this issue, the same authors proposed a Multi-Perspective Cross-Class (MPCC) domain adaptation method [85] based on the baseline method CAL [15]. MPCC conducts feature

TABLE II: Summary of representative deep learning-based logo detection methods.

Method type	Method	Pipeline	Task	Strategy	Loss function	Year
RCNNs	DeepLogo-DRCN [14]	RCNN Fast RCNN SPPnet	Regular logo detection	-	-	2015
	BD-FRCN [60]	Fast RCNN	Regular logo detection	Transfer learning	-	2016
	Improved Faster RCNN [57]	Faster RCNN	Small logo detection	Preset anchor boxes	-	2017
	Deep Region-based Convolutional Networks [61]	Faster RCNN	Regular logo detection	Transfer learning K-means clustering Data augmentation	-	
	Video logo detector [22]	Fast RCNN	Video logo detection	Homogeneity enhancement Mutual enhancement	-	2021
	Faster RCNN+ResNet-50 [5]	Faster RCNN	Long tail logo detection Small logo detection	Data augmentation Category balance	EQLv2 Seesaw Loss	
	Cascade detectoRS [6]	Cascade RCNN	Long tail logo detection Small logo detection	Data augmentation Multi-scale training	EQLv2	
	Cascade RCNN+ Res2Net101 [7]	Cascade RCNN	Long tail logo detection	Data augmentation Gradient balance Data Sampling	EQLv2	
Green Hand [8]	DetectoRS	Long tail logo detection Small logo detection	Data augmentation Resampling Weighted boxes	EQLv2		
YOLOs	Improved YOLOv3 [72]	YOLOv3	Small logo detection	Hard example re-training	-	2019
	Scene recognition CNN [24]	YOLOv3	Regular logo detection	-	-	2020
	Improved YOLOv2 [71]	YOLOv2	Regular logo detection	Separable convolution Multi-scale features fusion	Confidence error loss Coordinate error loss Prediction box loss	
	Improved YOLOv2 [79]	YOLOv2	Multi-scale logo detection	Preset anchor boxes K-means clustering	-	
	Logo-Yolo [17]	YOLOv3	Regular logo detection	Improved losses K-means clustering	Focal loss CIoU loss	2021
	Scaled YOLOv4 [80]	YOLOv4	Regular logo detection	-	-	
SSDs	Separable-VLD [73]	YOLO	Small logo detection	Separable convolution	-	2021
	SVLD [25]	SSD	Multi-scale logo detection	Preset anchor boxes	-	2019
	SSD InceptionV2 [58]	SSD	Regular logo detection	Preset anchor boxes	-	
FPNs	Brand Net [28]	-	Small logo detection	Soft mask attention Weight transfer Anchor refinement	Class-aware smooth L1 Class-agnostic smooth L1 Cross-entropy loss	2020
	OSF-Logo [76]	-	Multi-scale logo detection	Deformable convolution Up-sampling operator	-	2021
	MFDNet [16]	-	Multi-scale logo detection	Multi-scale feature fusion Deformable learning	Cross-entropy loss	
	DETR-FP [77]	DETR	Small logo detection	Model fusion	Hungarian loss Generalized IoU loss	
Others	SLST [29]	Faster RCNN	Weakly supervised logo detection	Incremental learning Self-Training	-	2017
	SCL [21]	Faster RCNN	Few shot logo detection	Synthetic context logo	-	
	CAL [15]	Faster RCNN YOLOv2	Weakly supervised logo detection	Context adversarial learning	Softmax cross-entropy loss Conditional adversarial loss	2018
	Weakly supervised learning of CNN [81]	DCNN	Weakly supervised logo detection	Generate saliency map GrabCut segmentation	Softmax loss	2021
	Airline logo detection system [82]	AttentionMask	Complex scenes logo detection	Data augmentation	Cross-entropy loss	
	LogoNet [83]	-	Complex scenes logo detection	Spatial attention	-	
	Deep attention networks [84]	-	Regular logo detection	Domain adaptation Nonlocal block	-	
	MPCC [85]	Faster RCNN	Few shot logo detection	Domain adaptation Data augmentation	Softmax cross-entropy loss	
DTAL [86]	DCNN	Video logo detection Few shot logo detection	Active learning Transfer learning	Meta-class loss	2022	

distribution alignment in the data augmentation principle from two perspectives. One is to align the feature distribution between the synthetic logo image of 1-shot icon supervised classes and the authentic logo image of the fully supervised class. The other is to align the feature distribution between the logo and non-logo images. This mitigates the domain shift problem between model training and testing on 1-shot icon supervised logo classes and reduces the model's overfitting to the fully labeled logo classes. The final combination of MPCC with Faster R-CNN achieved good results.

Training a logo detector usually requires a large amount of labeled data, and labeling logo data is time-consuming. Therefore, weakly supervised learning is a vital strategy to solve this issue. Kumar *et al.* [81] proposed a method for logo detection by using weakly supervised learning of CNN to

generate a deep saliency map, which is generated by a single back-propagation of a trained Deep CNN. The authors also used an interactive Grabcut algorithm to calculate the salient segmented regions of the image. However, this method is not sufficiently modeled to detect multiple brand logos in the same image.

Logo detectors usually perform poorly in classes with a small number of samples. To this end, Yohannes *et al.* [84] designed a framework consisting of a domain adaptation that reduces the loss function between source-target datasets and also represents important source features adopted by the target dataset. The authors add nonlocal blocks and attention mechanisms to achieve a decent performance of logo detection. Similarly, Su *et al.* [86] developed a deep transfer active learning algorithm named DTAL to select the most valuable

samples such that we can label the smallest number of samples to achieve maximum performance improvements in training detection models.

When the image is affected by unfavorable factors such as illumination, rotation, occlusion, etc., the performance of the detector will be significantly reduced. In recent years, the attention mechanisms have attracted increasing attention to solving this issue in logo detection [82, 83]. For example, Wilms *et al.* [82] took the airline logos as an example and proposed a logo detection system under adverse conditions. The authors adopt the object proposal generation system AttentionMask [87]. Since the aviation system logo is relatively large, the AttentionMask system removes the scale of small objects to improve execution efficiency and reduce false positives. They also used a data augmentation solution to simulate the effects of severe weather to diversify the training data processing effects. The experimental results show that the proposed strategy can achieve good performance in detecting the logo in complex real-world environments. However, the data obtained under real-world conditions are not as ideal as the data generated by data augmentation, so the performance of the model in detecting images in real-world conditions will be degraded. Considering that locating logos in complex scenarios is challenging due to the large variety of types and appearance of logos, Jain *et al.* [83] proposed a logo detection framework called LogoNet, which includes a spatial attention module. LogoNet can capture rich spatial information and focus more precisely on the logo object within an image. LogoNet achieves a significant performance gain within considerable computation time.

In order to analyze current state-of-the-art deep learning-based methods more comprehensively, the representative models are presented in chronological order in Table II, and the experimental results of these models on three popular benchmark datasets, namely Flickrlogos-32, QMUL-OpenLogo, and Open Brands, are listed in Table III, Table IV, and Table V respectively.

#### IV. APPLICATIONS

Logo detection is widely used in various applications, such as intellectual property protection, autonomous driving, and product branding. In this section, we describe the representative applications of logo detection in detail.

##### A. Brand Monitoring

The most obvious use case for logo detection is brand monitoring, which includes brand protection, brand recommendation, and brand identification. Logo plays an essential role in business marketing as a unique brand identity. However, there are many types of brands in real life, and there may be subtle logo differences between the two products. Inter-class similarities and intra-class differences will greatly increase the difficulty of detection. In addition, images may have highly diverse context, illumination, projection transformation, and resolution. Therefore, how efficiently detecting brands in images is a challenging task. Currently, there is a lot of work on brand identity [3, 28, 58, 60]. For brand logos,

**TABLE III:** Performance comparison of logo detectors on the FlickrLogos-32 benchmark.

Method	mAP(%)	Year
FRCN [46]	74.4	2015
BD-FRCN-M [60]	73.5	2016
Video Logo Detector [22]	78.6	2017
Faster RCNN+VGG16_D2_M3 [61]	90.3	2017
Faster RCNN+CAL [15]	74.9	2018
Deep Saliency Map [81]	75.8	2020
Logo-Yolo [17]	76.1	2020
LogoNet [83]	82.2	2021
OSF-Logo [76]	87.0	2021
RetinaNet [59]	40.0	2021
RCNN [59]	65.0	2021
Faster RCNN [59]	74.0	2021
Scaled YOLOv4 [80]	80.4	2021
MFDNet [16]	86.2	2021

**TABLE IV:** Performance comparison of logo detectors on the QMUL-OpenLogo benchmark.

Method	mAP(%)	Year
YOLOv2+CAL [15]	49.2	2018
Faster RCNN+CAL [15]	51.0	2018
Logo-Yolo [17]	53.2	2020
Faster RCNN+CAL+MPCC [85]	49.4	2021
OSF-Logo [76]	53.3	2021
Scaled YOLOv4 [80]	61.9	2021
MFDNet [16]	51.3	2021

**TABLE V:** Performance comparison of logo detectors on the Open Brands benchmark.

Method	mAP(%)	Year
Brand Net (SMA) [28]	60.4	2020
Faster RCNN+RFS+MST [5]	64.6	2021
Cascade RCNN+Soft NMS [6]	65.1	2021
Green Hand [8]	65.5	2021
Cascade RCNN+DCN v2 [7]	70.2	2021

the image usually includes some textual description. Textual information is an important source of information for brand identity. Hu *et al.* [3] proposed a multimodal fusion framework for logo detection. The framework combines image-based logo recognition with contextual features for logo detection using a natural language model. Additional contextual information can alleviate the limitations of detection. The performance of this model for logo detection has been improved, but there are still shortcomings in positioning.

##### B. Intelligent Transportation

In intelligent transportation, vehicle logo detection is significantly growing as it can effectively assist vehicle management. In addition, due to the increasing number of vehicle violations and traffic accidents, the realization of intelligent transportation systems is crucial. However, in the real world, the detection of vehicle logos is seriously disturbed due to occlusion, illumination, and low image resolution. Therefore, an efficient vehicle logo detection system is essential. In recent years, methods for vehicle logo detection have been proposed successively [23, 34, 37–39, 72, 79, 88]. Lu *et al.* [48] designed a feature extraction module VLF-Net and category-consistent mask learning module for vehicle logo detection. Yu *et al.* [1] proposed a cascaded deep convolutional neural






Fig. 7: The architecture for video logo detection [22].

network to detect vehicles without relying on the presence of license plates. The network is a two-stage framework including two components: a region proposal network and a convolutional capsule network. The former is responsible for generating region proposals that may contain vehicle logos, while the latter is responsible for classifying the proposals into background and vehicle logos. Surwase *et al.* [2] proposed a multi-scale multi-stream deep network for vehicle logo detection. The network processes the input image through a multi-scale stream to extract robust features, followed by logo recognition. The network follows a knowledge sharing strategy, where the learned features are shared on each stream of the network.

### C. Copyright and Trademark Compliance

With the development of global e-commerce platforms, the logos of major brands have become an important element in the e-commerce market. Some attackers use illegal means to infringe on the original author, so protecting intellectual property rights has also become a focus. Logo detection plays a vital role in preventing the increasing number of counterfeit transaction attempts online [5–8, 33, 89, 90]. Infringement detection of logos has been studied for images and videos. Chen *et al.* [5] built a highly optimized and robust detector by using techniques such as data augmentation for the detection of logos (515 categories) in e-commerce images. Patalappa *et al.* [4] extended the dataset through data augmentation techniques. They applied the SSD algorithm to detect broadcast logos in the context of broadcast and broadband content piracy and proved the effectiveness of the application of SSD in content piracy video analysis monitoring tasks. An efficient way to identify the source of a web video is to detect some specified logos. In order to identify the source of illegal videos, Ye *et al.* [91] proposed a logo detection system GeLoGo to detect logos in Web-scale videos. The system consists of four main modules: the keyframe module, the proposal module, the spatial verification module, and the temporal verification module. The keyframe module first extracts several frames with short fragment detection, which can significantly reduce the data. Secondly, the proposal module extracts candidate boxes through a set of pre-trained identity detectors. Then,

the spatial validation module detects logos through the ResNet network. Finally, the temporal verification module detects the detection result by detecting the recognition position.

### D. Document Categorization

A logo often appears in commercial documents and can be used as a statement of ownership of the document. Automatic logo detection is growing due to the increasing requirements of intelligent document image analysis and retrieval [92–94]. Alaei *et al.* [95] proposed a complete system for logo detection in document images. They proposed a template-based recognition strategy for under or over-segmentation problems that may arise during detection. In order to speed up the matching of templates in the recognition phase, a search space reduction strategy that utilizes the geometric properties of logo-patches and template logo-models is proposed to reduce the number of template logo-models. Zhu *et al.* [96] proposed a multi-scale method for document image logo detection and extraction. The authors used an augmentation strategy across multiple image scales to classify and localize logos accurately.

### E. Other Applications

Logo detection can offer various benefits for advertisers looking to improve their marketing strategies effectively. As shown in Fig. 7, Liao *et al.* [22] proposed a video logo detection framework that used a mutual-enhanced approach to improve logo detection through the information obtained from other simultaneously occurred logos. Based on the Fast R-CNN model, a uniformity-enhanced reordering method is proposed to improve the accuracy of in-frame region suggestions by analyzing the features of logos in videos. In addition, they proposed a frame propagation enhancement method to assist in the detection of adjacent frames. Finally, the effectiveness of the method is demonstrated on the FlickrLogos-32 dataset and the video dataset. Recently, food logo detection [16] has become more popular because it has many valuable applications, such as food brand management and displaying nutritional information. Logo detection is also used in other areas, such as video semantic annotation [40, 80, 97], and noise recognition [36, 45, 98, 99]. Since the TV logo photographed is susceptible to illumination, occlusion, noise, and




Fig. 8: Distinctive properties of logos.

other factors, the TV logo may only take up a small part of each image. To this end, Pan *et al.* [100] proposed an efficient CNN to solve this problem. They used the maximum stable extremal region (MSER) algorithm to extract candidate frames. Since this algorithm tends to produce a large number of candidate frames without TV logos, they designed certain geometric constraints to remove non-logo objects. Finally, the images were fed into the CNN network for classification and achieved good results.

## V. CHALLENGES AND FUTURE DIRECTIONS

### A. Challenges

Logo detection has received more attention in the last few years for its wide applications. However, robust and accurate logo detection is still challenging in real-world scenarios because the logo images have distinctive properties, which may form significant obstacles to current progress. We try to summarize them as following: (1) *Small size*: Unlike generic objects, logos tend to be small in size, making it difficult to distinguish them from contexts, especially the complex background. Although contextual information is crucial in small object detection because small objects carry limited information [101], it is not always beneficial for logo detection, especially when it is too complex and unrelated to the target logo, as shown in Fig. 8(a). We know that in the deep learning-based detection architecture, different layers of feature maps with various spatial resolutions are produced due to pooling and subsampling processes. Early-layer feature maps represent small reception fields but lack high-level semantic information critical for logo detection. In contrast, high-level feature maps help identify large logos but may not detect smaller ones. (2) *Highly diverse backgrounds*: A logo is usually associated with other visible entities, like a particular service or product. Thus, a logo may appear in various situations superimposed

on objects such as geometrical renderings, shirts of persons, jerseys of players, boards of shops, billboards, or posters on sports playfields. As shown in Fig. 8 (b), a brand like Nike may serve many types of products, such as jackets, shoes, or trousers, resulting in the same logo being attached to a variety of different objects, which poses challenges to designing a robust logo detector when considering image statistics from the entire image. (3) *Sub-branding*: Sub-branding is often considered when a company releases a new product. Sub-brand detection facilitates brand monitoring but suffers from the same problems as fine-grained classification, such as subtle differences between sub-brands and parent brands and between sub-brands. In real logo detection, some sub-brands are treated as logos different from the parent brand or other sub-brands because they have customer expectations and personalities that are different from the parent brand. Thus, the parent brand and its sub-brands usually have remarkably similar context information (background, packaging, etc., as shown in Fig. 8(c)). When considering image-level feature maps, in this case, there are probably several remarkably similar feature maps extracted from different logo images, which challenges identifying different sub-brand logos accurately when using the deep learning-based detector.

Many approaches to tackle logo detection tasks have been developed based on object detection methods and have achieved promising results, but there is still much room for improvement. For example, [72] proposed a vehicle logo detection system based on YOLOv3. Though the performance of small logo detection has been improved to a certain extent, it fails to accurately detect small logos with complex letter patterns. [57] designed an improved anchor-based scheme for small logos by utilizing higher resolution feature maps. However, it is too computationally expensive for constrained scenarios and too slow for real-time applications due to adopting a two-phase detection strategy. It is worth mentioning that the best detection performance only reaches 61.9% of mAP on QMUL-OpenLogo [80], in which the logo detector is designed based on YOLOv4. Therefore, simply borrowing the existing detectors from general object detection is considered insufficient for logo detection. Designing a new detection paradigm that is suitable for logos is essential.

### B. Future Directions

Some future research directions in logo detection are as follows:

**Lightweight logo detection**: Lightweight networks are designed to reduce model complexity further while maintaining model accuracy. With the rapid development of mobile terminals such as mobile phones and computers, people pay more attention to lightweight detectors. Lightweight logo detection can help consumers quickly identify and accurately search for the products they need and thus can significantly improve the efficiency of online shopping. Although significant efforts have been made recently, the speed gap between the machine and the human eye is still huge. The detection accuracy is also insufficient, especially for small logos. Therefore, improving the accuracy of lightweight logo detectors is one of the future development trends.

**Weakly supervised logo detection:** A fully supervised logo detector must be trained on fully labeled large-scale logo datasets. However, the labeling of existing datasets is mainly done manually, which poses a challenge to the generalization and robustness of existing models due to the problem of data quality. With the rapid growth of logo data volume, data annotation costs are getting higher and higher. Developing weakly supervised logo detection techniques that only use image-level annotations or partial bounding box annotations to train logo detectors significantly reduces costs and improves detection flexibility. Therefore, developing weakly supervised logo detection methods without fully labeled training data is an important issue for future research.

**Video logo detection:** Logo promotion exists in most video advertisements. Accurate and reasonable advertising is targets businesses, so it is essential to identify the target logo effectively. Current logo detectors are commonly used to detect logos of individual images, which may lead to a lack of correlation between consecutive images. In addition, there are problems such as motion blur and target occlusion in logo detection of videos, which can highly affect the performance of the detector. There are already methods trying to detect video logos. Currently, there are methods [22, 86] trying to detect video logos, but they have not achieved satisfactory results. Therefore, it is an important research direction to improve logo detection by utilizing temporal and spatial correlations.

**Tiny logo detection:** Tiny logos contain insufficient information, making it more challenging to extract discriminative features. Meanwhile, tiny logos contain relatively few samples and thus are easily disturbed by environmental factors. Numerous real-world tiny logos may have highly diverse contexts, which can cause the same logo to appear very different in different real scenarios. Observing the results of existing detection methods on tiny logos, we can find that the performance of this methods [72, 73, 77] is unsatisfactory in real scenarios.

**Long tail logo detection:** With the rapid development of society, some enterprises are currently leading the way, and their enterprise logos naturally often appear in front of the public. In contrast, the logos of most small enterprises are not paid much attention to because they appear less. The long-tail distribution of logos exists all the time in reality. Some logo classes contain a large number of samples, while others contain few samples, making it difficult for logo detectors to detect logo classes with few samples. In previous logo detection methods, there is little focus on the long-tailed distribution in logo images. Therefore, it is one of the future tasks to utilize the unbalanced data to train efficient and accurate detectors.

**Incremental logo detection:** As a company's signature or symbol, the logo will continue to increase as the number of companies increases. Therefore, the logo detector must learn new logos. However, retraining the logo detector is time-consuming and resource-intensive by discarding the previously learned knowledge. Incremental learning enables a system to continuously learn new knowledge from new samples while retaining most previously learned knowledge without catastrophic forgetting. It can reduce the complexity of the model to a certain extent, thereby reducing the training cost of

the model. However, no incremental learning method currently can show good performance under all conditions. Therefore, incremental learning for logo detection is one of the future research directions.

In fact, existing studies generally assume close-environment scenarios. For example, the data distribution of logo datasets is invariable, and all the training data have known classes and fine-grained bounding box annotations in advance. Although Su *et al.* [15] proposed an assumption to simulate the open deployment, they mainly focus on the problem of limited logo data by presenting a context adversarial learning approach to generate context-consistent synthetic training data automatically. How to enable the trained model to be updated according to emerging new logo classes or data distribution change, or even we hardly know what changes is an essential requirement in open-environment.

## VI. CONCLUSION

In this work, we offer a comprehensive survey of previous and current approaches that helps logo detection. We mainly review the recent advances in deep learning-based logo detection by summarizing classical solutions. In addition, we comprehensively review the commonly used datasets, summarize the related applications of logo detection, and predict future research directions. Although the achievement of logo detection has been effective recently, there is still much room for further development. We hope this paper will better inform readers about the current development of logo detection and inspire more people to get involved in logo detection.

## REFERENCES

- [1] Y. Yu, H. Guan, D. Li, and C. Yu, "A cascaded deep convolutional network for vehicle logo recognition from frontal and rear images of vehicles," *IEEE Transactions on Intelligent Transportation Systems*, vol. 22, no. 2, pp. 758–771, 2021.
- [2] S. Surwase and M. Pawar, "Multi-scale multi-stream deep network for car logo recognition," *Evolutionary Intelligence*, pp. 1–8, 2021.
- [3] C. Hu, Q. Li, Z. Zhang, K. Chang, and R. Zhang, "A multimodal fusion framework for brand recognition from product image and context," in *IEEE International Conference on Multimedia & Expo Workshops*, 2020, pp. 1–4.
- [4] K. K. J. Patalappa and S. M. Chandramouli, "Robust recognition of logo under makeover in the context of content piracy," *Global Transitions Proceedings*, vol. 2, no. 2, pp. 421–428, 2021.
- [5] H. Chen, X. Li, Z. Wang, and X. Hu, "Robust logo detection in e-commerce images by data augmentation," in *Proceedings of the 29th ACM International Conference on Multimedia*, 2021, pp. 4789–4793.
- [6] X. Jia, H. Yan, Y. Wu, X. Wei, X. Cao, and Y. Zhang, "An effective and robust detector for logo detection," *arXiv preprint arXiv:2108.00422*, 2021.
- [7] F. Leng, "A gradient balancing approach for robust logo detection," in *Proceedings of the 29th ACM International Conference on Multimedia*, 2021, pp. 4765–4769.
- [8] W. Xu, Y. Liu, and D. Lin, "A simple and effective baseline for robust logo detection," in *Proceedings of the 29th ACM International Conference on Multimedia*, 2021, pp. 4784–4788.
- [9] K. Tong, K. W. Cheung, and X. Yu, "ICME 2022 few-shot logo detection top 9 solution," *arXiv preprint arXiv:2206.11462*, 2022.
- [10] H. Sahbi, L. Ballan, G. Serra, and A. Bimbo, "Context-dependent logo matching and recognition," *IEEE Transactions on Image Processing*, vol. 22, no. 3, pp. 1018–1031, 2013.
- [11] A. Krizhevsky, I. Sutskever, and G. E. Hinton, "Imagenet classification with deep convolutional neural networks," *Communications of the ACM*, vol. 60, no. 6, pp. 84–90, 2012.
- [12] A. Joly and O. Buisson, "Logo retrieval with a contrario visual query expansion," in *Proceedings of the 17th ACM International Conference on Multimedia*, 2009, pp. 581–584.

- [13] S. Romberg, L. G. Pueyo, R. Lienhart, and V. Z. Roelof, "Scalable logo recognition in real-world images," in *Proceedings of the 1st ACM International Conference on Multimedia Retrieval*, 2011, pp. 1–8.
- [14] S. C. H. Hoi, X. Wu, H. Liu, Y. Wu, H. Wang, H. Xue, and Q. Wu, "Logo-Net: Large-scale deep logo detection and brand recognition with deep region-based convolutional networks," *arXiv preprint arXiv:1511.02462*, 2015.
- [15] H. Su, X. Zhu, and S. Gong, "Open logo detection challenge," in *British Machine Vision Conference*, 2018, pp. 111–119.
- [16] Q. Hou, W. Min, J. Wang, S. Hou, Y. Zheng, and S. Jiang, "FoodLogoDet-1500: A dataset for large-scale food logo detection via multi-scale feature decoupling network," in *Proceedings of the 29th ACM International Conference on Multimedia*, 2021, pp. 4670–4679.
- [17] J. Wang, W. Min, S. Hou, S. Ma, Y. Zheng, and S. Jiang, "LogoDet-3K: A large-scale image dataset for logo detection," *ACM Transactions on Multimedia Computing, Communications, and Applications*, vol. 18, no. 1, pp. 1–19, 2022.
- [18] C. Li, I. Fehérvári, X. Zhao, I. Macêdo, and S. Appalaraju, "SeeTek: Very large-scale open-set logo recognition with text-aware metric learning," in *IEEE/CVF Winter Conference on Applications of Computer Vision*, 2022, pp. 587–596.
- [19] Y. Kalantidis, L. G. Pueyo, M. Trevisiol, V. Z. Roelof, and Y. Avrithis, "Scalable triangulation-based logo recognition," in *Proceedings of the 1st ACM International Conference on Multimedia Retrieval*, 2011, pp. 1–7.
- [20] S. Bianco, M. Buzzelli, D. Mazzini, and R. Schettini, "Deep learning for logo recognition," *Neurocomputing*, vol. 245, pp. 23–30, 2017.
- [21] H. Su, X. Zhu, and S. Gong, "Deep learning logo detection with data expansion by synthesising context," in *IEEE Winter Conference on Applications of Computer Vision*, 2017, pp. 530–539.
- [22] Y. Liao, X. Lu, C. Zhang, Y. Wang, and Z. Tang, "Mutual enhancement for detection of multiple logos in sports videos," in *IEEE International Conference on Computer Vision*, 2017, pp. 4856–4865.
- [23] J. Liu, F. Shen, M. Wei, Y. Zhang, H. Zeng, J. Zhu, and C. Cai, "A large-scale benchmark for vehicle logo recognition," in *4th International Conference on Image, Vision and Computing*, 2019, pp. 479–483.
- [24] A. Kuznetsov and A. V. Savchenko, "A new sport teams logo dataset for detection tasks," in *International Conference on Computer Vision and Graphics*, 2020, pp. 87–97.
- [25] J. Zhang, L. Chen, C. Bo, and S. Yang, "Multi-scale vehicle logo detector," *Mobile Networks and Applications*, vol. 26, no. 1, pp. 67–76, 2021.
- [26] A. Tüzkö, C. Herrmann, D. Manger, and J. Beyerer, "Open set logo detection and retrieval," in *International Conference on Computer Vision Theory and Applications*, 2018, pp. 284–292.
- [27] I. Fehérvári and S. Appalaraju, "Scalable logo recognition using proxies," in *IEEE Winter Conference on Applications of Computer Vision*, 2019, pp. 715–725.
- [28] X. Jin, W. Su, R. Zhang, Y. He, and H. Xue, "The open brands dataset: Unified brand detection and recognition at scale," in *IEEE International Conference on Acoustics, Speech and Signal Processing*, 2020, pp. 4387–4391.
- [29] H. Su, S. Gong, and X. Zhu, "Weblogo-2M: Scalable logo detection by deep learning from the web," in *Proceedings of the IEEE International Conference on Computer Vision Workshops*, 2017, pp. 270–279.
- [30] J. Wang, W. Min, S. Hou, S. Ma, Y. Zheng, H. Wang, and S. Jiang, "Logo-2K+: A large-scale logo dataset for scalable logo classification," in *Proceedings of the AAAI Conference on Artificial Intelligence*, 2020, pp. 6194–6201.
- [31] M. Everingham, L. V. Gool, C. K. I. Williams, J. M. Winn, and A. Zisserman, "The pascal visual object classes (VOC) challenge," *International Journal of Computer Vision*, vol. 88, no. 2, pp. 303–338, 2009.
- [32] C. Cortes and V. N. Vapnik, "Support-vector networks," *Machine Learning*, vol. 20, pp. 273–297, 1995.
- [33] B. Lei, V. L. Thing, Y. Chen, and W. Y. Lim, "Logo classification with edge-based daisy descriptor," in *IEEE International Symposium on Multimedia*, 2012, pp. 222–228.
- [34] B. Zhang and H. Pan, "Reliable classification of vehicle logos by an improved local-mean based classifier," in *6th International Congress on Image and Signal Processing*, 2013, pp. 176–180.
- [35] P. Carvalho, A. Pereira, and P. Viana, "Automatic TV logo identification for advertisement detection without prior data," *Applied Sciences*, vol. 11, no. 16, pp. 74–94, 2021.
- [36] M. A. M. Sathiseelan, O. P. Paradis, R. Rai, S. V. Pandurangi, M. Y. Vutukuru, S. Taheri, and N. Asadizanjani, "Logo classification and data augmentation techniques for PCB assurance and counterfeit detection," in *Conference Proceedings from the 47th International Symposium for Testing and Failure Analysis*, 2021, pp. 12–19.
- [37] Z. Xiang, Y. Zou, X. Zhou, and X. Huang, "Robust vehicle logo recognition based on locally collaborative representation with principal components," in *Sixth International Conference on Information Science and Technology*, 2016, pp. 487–491.
- [38] S. Gopinathan and G. Lalitha, "Vehicle logo recognition using enhanced learning : VLR recognition," in *2nd International Conference on I-SMAC*, 2018, pp. 707–712.
- [39] C. Pan, Z. Yan, X. Xu, M. Sun, J. Shao, and D. Wu, "Vehicle logo recognition based on deep learning architecture in video surveillance for intelligent traffic system," in *IET International Conference on Smart and Sustainable City*, 2013, pp. 123–126.
- [40] F. Zhang, L. Cao, and D. M. Zhang, "TV logo dataset and annotations for the convolution neural network," in *10th International Congress on Image and Signal Processing, BioMedical Engineering and Informatics*, 2017, pp. 1–6.
- [41] S. Hou, J. Lin, S. Zhou, M. Qin, W. Jia, and Y. Zheng, "Deep hierarchical representation from classifying logo-405," *Complexity*, vol. 29, no. 6, pp. 1–12, 2017.
- [42] A. J. Gallego, A. Pertusa, and M. Bernabeu, "Multi-label logo classification using convolutional neural networks," in *Pattern Recognition and Image Analysis*, 2019, pp. 485–497.
- [43] M. Karimi and A. Behrad, "Logo recognition by combining deep convolutional models in a parallel structure," in *4th International Conference on Pattern Recognition and Image Analysis*, 2019, pp. 216–221.
- [44] M. Bernabeu, A. J. Gallego, and A. Pertusa, "Multi-label logo recognition and retrieval based on weighted fusion of neural features," *arXiv preprint arXiv:2205.05419*, 2022.
- [45] Hendrick, C. M. Wang, Aripriharta, C. G. Jhe, P. C. Tsu, and G. J. Jong, "The halal logo classification by using nvidia digits," in *International Conference on Applied Information Technology and Innovation*, 2018, pp. 162–165.
- [46] F. N. Iandola, A. Shen, P. Gao, and K. Keutzer, "Deeplogo: Hitting logo recognition with the deep neural network hammer," *arXiv preprint arXiv:1510.02131*, 2015.
- [47] W. Yousaf, A. Umar, S. H. Shirazi, Z. Khan, and M. Zaka, "Patch-CNN: Deep learning for logo detection and brand recognition," *Journal of Intelligent and Fuzzy Systems*, vol. 40, no. 2, pp. 1–14, 2021.
- [48] W. Lu, H. Zhao, Q. He, H. Huang, and X. Jin, "Category-consistent deep network learning for accurate vehicle logo recognition," *Neurocomputing*, vol. 463, pp. 623–636, 2021.
- [49] R. Boia, C. Florea, and L. Florea, "Elliptical ASIFT agglomeration in class prototype for logo detection," in *Proceedings of the British Machine Vision Conference*, 2015, pp. 115.1–115.12.
- [50] C. Wan, Z. Zhao, X. Guo, and A. Cai, "Tree-based shape descriptor for scalable logo detection," in *Visual Communications and Image Processing*, 2013, pp. 1–6.
- [51] C. Constantinopoulos, E. Meinhardt, Y. Liu, and V. Caselles, "A robust pipeline for logo detection," in *IEEE International Conference on Multimedia and Expo*, 2011, pp. 1–6.
- [52] J. Revaud, M. Douze, and C. Schmid, "Correlation-based burstiness for logo retrieval," in *Proceedings of the 20th ACM International Conference on Multimedia*, 2012, p. 965968.
- [53] R. B. Girshick, J. Donahue, T. Darrell, and J. Malik, "Rich feature hierarchies for accurate object detection and semantic segmentation," in *IEEE Conference on Computer Vision and Pattern Recognition*, 2014, pp. 580–587.
- [54] J. R. R. Uijlings, K. E. A. van de Sande, T. Gevers, and A. W. M. Smeulders, "Selective search for object recognition," *International Journal of Computer Vision*, vol. 104, pp. 154–171, 2013.
- [55] R. B. Girshick, "Fast R-CNN," in *IEEE International Conference on Computer Vision*, 2015, pp. 1440–1448.
- [56] S. Ren, K. He, R. B. Girshick, and J. Sun, "Faster R-CNN: Towards real-time object detection with region proposal networks," *IEEE Transactions on Pattern Analysis and Machine Intelligence*, vol. 39, no. 6, pp. 1137–1149, 2015.
- [57] C. Eggert, D. Zecha, S. Brehm, and R. Lienhart, "Improving small object proposals for company logo detection," in *Proceedings of the 2017 ACM on International Conference on Multimedia Retrieval*, 2017, p. 167174.
- [58] O. Ortí, R. Tous, M. Gomez, J. Poveda, L. Cruz, and O. Wüst, "Real-time logo detection in brand-related social media images," in *Advances in Computational Intelligence*, 2019, pp. 125–136.
- [59] S. Sahel, M. Alsahafi, M. Alghamdi, and T. Alsabait, "Logo detection

- using deep learning with pretrained CNN models,” *Engineering, Technology & Applied Science Research*, vol. 11, no. 1, pp. 6724–6729, 2021.
- [60] G. Oliveira, X. Frazão, A. Pimentel, and B. Ribeiro, “Automatic graphic logo detection via fast region-based convolutional networks,” in *International Joint Conference on Neural Networks*, 2016, pp. 985–991.
- [61] Y. Li, Q. Shi, J. Deng, and F. Su, “Graphic logo detection with deep region-based convolutional networks,” in *IEEE Visual Communications and Image Processing*, 2017, pp. 1–4.
- [62] J. Redmon, S. K. Divvala, R. B. Girshick, and A. Farhadi, “You only look once: Unified, real-time object detection,” in *IEEE Conference on Computer Vision and Pattern Recognition*, 2016, pp. 779–788.
- [63] J. Redmon and A. Farhadi, “YOLO9000: Better, faster, stronger,” in *IEEE Conference on Computer Vision and Pattern Recognition*, 2017, pp. 6517–6525.
- [64] J. Redmon and A. Farhadi, “YOLOv3: An incremental improvement,” *arXiv preprint arXiv:1804.02767*, 2018.
- [65] A. Bochkovskiy, C. Y. Wang, and H. Liao, “YOLOv4: Optimal speed and accuracy of object detection,” *arXiv preprint arXiv:2004.10934*, 2020.
- [66] Q. Chen, Y. Wang, T. Yang, X. Zhang, J. Cheng, and J. Sun, “You only look one-level feature,” in *IEEE/CVF Conference on Computer Vision and Pattern Recognition*, 2021, pp. 13 034–13 043.
- [67] C. Y. Wang, I. H. Yeh, and H. Liao, “You only learn one representation: Unified network for multiple tasks,” *arXiv preprint arXiv:2105.04206*, 2021.
- [68] Z. Ge, S. Liu, F. Wang, Z. Li, and J. Sun, “YOLOX: Exceeding yolo series in 2021,” *arXiv preprint arXiv:2107.08430*, 2021.
- [69] C. Li, L. Li, H. Jiang, K. Weng, Y. Geng, L. Li, Z. Ke, Q. Li, M. Cheng, W. Nie, Y. Li, B. Zhang, Y. Liang, L. Zhou, X. Xu, X. Chu, X. Wei, and X. Wei, “Yolov6: A single-stage object detection framework for industrial applications,” *arXiv preprint arXiv:2209.02976*, 2022.
- [70] C. Y. Wang, A. Bochkovskiy, and H. Liao, “Yolov7: Trainable bag-of-freebies sets new state-of-the-art for real-time object detectors,” *arXiv preprint arXiv:2207.02696*, 2022.
- [71] K. Yin, S. Hou, Y. Li, C. Li, and G. Yin, “A real-time vehicle logo detection method based on improved YOLOv2,” in *International Conference on Wireless Algorithms, Systems, and Applications*, 2020, pp. 666–677.
- [72] S. Yang, J. Zhang, C. Bo, M. Wang, and L. Chen, “Fast vehicle logo detection in complex scenes,” *Optics & Laser Technology*, vol. 110, pp. 196–201, 2019.
- [73] J. Zhang, S. Yang, C. Bo, and Z. Zhang, “Vehicle logo detection based on deep convolutional networks,” *Computers & Electrical Engineering*, vol. 90, p. 107004, 2021.
- [74] W. Liu, D. Anguelov, D. Erhan, C. Szegedy, S. E. Reed, C. Y. Fu, and A. C. Berg, “SSD: Single shot multibox detector,” in *European Conference on Computer Vision*, 2016, pp. 21–37.
- [75] T. Y. Lin, P. Dollár, R. B. Girshick, K. He, B. Hariharan, and S. J. Belongie, “Feature pyramid networks for object detection,” in *IEEE Conference on Computer Vision and Pattern Recognition*, 2017, pp. 936–944.
- [76] Y. Meng, S. Hou, J. Wang, W. Jia, Y. Zheng, and A. Karim, “An adaptive representation algorithm for multi-scale logo detection,” *Displays*, vol. 70, p. 102090, 2021.
- [77] D. A. Velazquez, J. M. Gonfaus, P. Rodríguez, F. X. Roca, S. Ozawa, and J. González, “Logo detection with no priors,” *IEEE Access*, vol. 9, pp. 106 998–107 011, 2021.
- [78] N. Carion, F. Massa, G. Synnaeve, N. Usunier, A. Kirillov, and S. Zagoruyko, “End-to-end object detection with transformers,” in *European Conference on Computer Vision*, 2020, pp. 213–229.
- [79] S. Yang, C. Bo, J. Zhang, and M. Wang, “Vehicle logo detection based on modified YOLOv2,” in *2nd EAI International Conference on Robotic Sensor Networks*, 2020, pp. 75–86.
- [80] K. Paleček and J. Chaloupka, “Logo detection and identification in system for audio-visual broadcast transcription,” in *44th International Conference on Telecommunications and Signal Processing*, 2021, pp. 357–360.
- [81] G. Kumar, P. Keserwani, P. P. Roy, and D. P. Dogra, “Logo detection using weakly supervised saliency map,” *Multimedia Tools and Applications*, vol. 80, pp. 4341–4365, 2021.
- [82] C. Wilms, R. Heid, M. A. Sadeghi, A. Ribbrock, and S. Frintrop, “Which airline is this? Airline logo detection in real-world weather conditions,” in *25th International Conference on Pattern Recognition*, 2021, pp. 4996–5003.
- [83] R. K. Jain, T. Watasue, T. Nakagawa, S. Takahiro, Y. Iwamoto, R. Xiang, and Y. W. Chen, “LogoNet: Layer-aggregated attention centerNet for logo detection,” in *IEEE International Conference on Consumer Electronics*, 2021, pp. 1–6.
- [84] E. Yohannes, C. Y. Lin, T. K. Shih, C. Y. Hong, A. Enkhbat, and F. Utaminigrum, “Domain adaptation deep attention network for automatic logo detection and recognition in google street view,” *IEEE Access*, vol. 9, pp. 102 623–102 635, 2021.
- [85] H. Su, S. Gong, and X. Zhu, “Multi-perspective cross-class domain adaptation for open logo detection,” *Computer Vision and Image Understanding*, vol. 204, p. 103156, 2021.
- [86] H. Su and G. Qiu, “Few shot transfer active learning for logo detection in sports video,” *SSRN Electronic Journal*, 2022.
- [87] C. Wilms and S. Frintrop, “AttentionMask: Attentive, efficient object proposal generation focusing on small objects,” in *Asian Conference on Computer Vision*, 2018, pp. 678–694.
- [88] S. Sotheeswaran and A. Ramanan, “A classifier-free codebook-based image classification of vehicle logos,” in *9th International Conference on Industrial and Information Systems*, 2014, pp. 1–6.
- [89] Y. Zhang, M. Zhu, D. Wang, and S. Feng, “Logo detection and recognition based on classification,” in *Web-Age Information Management*, 2014, pp. 805–816.
- [90] D. Guru and N. V. Kumar, “Symbolic representation and classification of logos,” in *Proceedings of International Conference on Computer Vision and Image Processing*, 2017, pp. 555–569.
- [91] Q. Ye, Z. Luo, X. Xiao, and S. Ge, “GeLogo: Detecting tv logos from web-scale videos,” in *IEEE Third International Conference on Multimedia Big Data*, 2017, pp. 250–251.
- [92] V. P. Le, M. Visani, D. C. Tran, and J. M. Ogier, “Improving logo spotting and matching for document categorization by a post-filter based on homography,” in *12th International Conference on Document Analysis and Recognition*, 2013, pp. 270–274.
- [93] T. A. Pham, M. Delalandre, and S. Barrat, “A contour-based method for logo detection,” in *International Conference on Document Analysis and Recognition*, 2011, pp. 718–722.
- [94] Z. Li, S. A. Matthias, and M. Neschen, “Fast logo detection and recognition in document images,” in *20th International Conference on Pattern Recognition*, 2010, pp. 2716–2719.
- [95] A. Alaei and M. Delalandre, “A complete logo detection/recognition system for document images,” in *11th IAPR International Workshop on Document Analysis Systems*, 2014, pp. 324–328.
- [96] G. Zhu and D. S. Doermann, “Automatic document logo detection,” in *9th International Conference on Document Analysis and Recognition*, 2007, pp. 864–868.
- [97] N. zay and B. Sankur, “Automatic TV logo detection and classification in broadcast videos,” in *17th European Signal Processing Conference*, 2009, pp. 839–843.
- [98] Y. Chen and V. L. L. Thing, “A noise-tolerant enhanced classification method for logo detection and brand classification,” in *FGIT-SecTech*, 2011, pp. 31–42.
- [99] P. Pimkote and T. Kangkachit, “Classification of alcohol brand logos using convolutional neural networks,” in *International Conference on Digital Arts, Media and Technology*, 2018, pp. 135–138.
- [100] D. Pan, P. Shi, Z. Qiu, Y. Sha, X. Zhongdi, and J. Zhoushao, “TV logo classification based on convolutional neural network,” in *IEEE International Conference on Information and Automation*, 2016, pp. 1793–1796.
- [101] S. K. Divvala, D. Hoiem, J. Hays, A. A. Efros, and M. Hebert, “An empirical study of context in object detection,” in *IEEE Conference on Computer Vision and Pattern Recognition*, 2009, pp. 1271–1278.