



SPEC® CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

SGI

SGI Altix ICE 8200
(Intel Xeon E5440, 2.83 GHz)

SPECfp®_rate2006 = 75.7

SPECfp_rate_base2006 = 68.1

CPU2006 license: 4


Test sponsor: SGI

Tested by: SGI

Test date: Jan-2007

Hardware Availability: Jan-2008

Software Availability: Nov-2007



Hardware

CPU Name: Intel Xeon E5440
 CPU Characteristics: Quad Core, 2.83GHz
 CPU MHz: 2833
 FPU: Integrated
 CPU(s) enabled: 8 cores, 2 chips, 4 cores/chip
 CPU(s) orderable: 1,2 chips
 Primary Cache: 32 KB I + 32 KB D on chip per core
 Secondary Cache: 12 MB I+D on chip per chip, 6 MB shared / 2 cores

Continued on next page

Software

Operating System: SUSE Linux Enterprise Server 10 (x86_64) SP1
 Kernel 2.6.16.46-0.12-smp
 Compiler: Intel C++ and Fortran Compiler for Linux
 Version 10.1, Build 20070913
 Auto Parallel: Yes
 File System: NFSv3 IPoIB
 System State: Multi-user, run level 3
 Base Pointers: 64-bit
 Peak Pointers: 32/64-bit

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

SGI

SGI Altix ICE 8200
(Intel Xeon E5440, 2.83 GHz)

SPECfp_rate2006 = 75.7

SPECfp_rate_base2006 = 68.1

CPU2006 license: 4

Test sponsor: SGI

Tested by: SGI

Test date: Jan-2007

Hardware Availability: Jan-2008

Software Availability: Nov-2007

L3 Cache: None
Other Cache: None
Memory: 16 GB (8*2GB PC2-5300 FB-DIMMs)
Disk Subsystem: 16 TB RAID 5+1
32 x 500 GB SATA (Seagate Barracuda 7200 rpm)
Other Hardware: None

Other Software: SGI ProPack 5 for Linux Service Pack 3
Binutils 2.17

Results Table

| Benchmark | Base | | | | | | | Peak | | | | | | |
|---------------|--------|-------------|-------------|-------------|-------------|-------------|-------------|--------|-------------|-------------|-------------|-------------|-------------|-------------|
| | Copies | Seconds | Ratio | Seconds | Ratio | Seconds | Ratio | Copies | Seconds | Ratio | Seconds | Ratio | Seconds | Ratio |
| 410.bwaves | 8 | 3078 | 35.3 | 3079 | 35.3 | 3079 | 35.3 | 4 | 1516 | 35.9 | 1520 | 35.8 | 1519 | 35.8 |
| 416.gamess | 8 | 965 | 162 | 968 | 162 | 966 | 162 | 8 | 950 | 165 | 951 | 165 | 952 | 164 |
| 433.milc | 8 | 2278 | 32.2 | 2283 | 32.2 | 2277 | 32.3 | 8 | 2318 | 31.7 | 2325 | 31.6 | 2311 | 31.8 |
| 434.zeusmp | 8 | 1056 | 68.9 | 1055 | 69.0 | 1055 | 69.0 | 8 | 1053 | 69.1 | 1055 | 69.0 | 1054 | 69.0 |
| 435.gromacs | 8 | 414 | 138 | 415 | 138 | 416 | 137 | 8 | 401 | 142 | 400 | 143 | 400 | 143 |
| 436.cactusADM | 8 | 1316 | 72.6 | 1312 | 72.8 | 1315 | 72.7 | 1 | 121 | 98.9 | 121 | 98.8 | 120 | 99.4 |
| 437.leslie3d | 8 | 2725 | 27.6 | 2724 | 27.6 | 2718 | 27.7 | 4 | 1330 | 28.3 | 1337 | 28.1 | 1336 | 28.2 |
| 444.namd | 8 | 539 | 119 | 540 | 119 | 540 | 119 | 8 | 535 | 120 | 543 | 118 | 536 | 120 |
| 447.dealII | 8 | 706 | 130 | 708 | 129 | 733 | 125 | 8 | 686 | 133 | 712 | 129 | 697 | 131 |
| 450.soplex | 8 | 1757 | 38.0 | 1756 | 38.0 | 1755 | 38.0 | 8 | 1572 | 42.4 | 1568 | 42.5 | 1570 | 42.5 |
| 453.povray | 8 | 221 | 193 | 219 | 194 | 219 | 195 | 8 | 189 | 225 | 187 | 227 | 187 | 227 |
| 454.calculix | 8 | 589 | 112 | 589 | 112 | 598 | 110 | 8 | 426 | 155 | 428 | 154 | 428 | 154 |
| 459.GemsFDTD | 8 | 2921 | 29.1 | 2939 | 28.9 | 2920 | 29.1 | 8 | 2935 | 28.9 | 2929 | 29.0 | 2933 | 28.9 |
| 465.tonto | 8 | 693 | 114 | 694 | 113 | 694 | 113 | 8 | 682 | 115 | 684 | 115 | 682 | 115 |
| 470.lbm | 8 | 4098 | 26.8 | 4099 | 26.8 | 4099 | 26.8 | 4 | 1306 | 42.1 | 1315 | 41.8 | 1330 | 41.3 |
| 481.wrf | 8 | 1732 | 51.6 | 1731 | 51.6 | 1722 | 51.9 | 8 | 1723 | 51.9 | 1723 | 51.9 | 1727 | 51.7 |
| 482.sphinx3 | 8 | 2161 | 72.2 | 2167 | 72.0 | 2154 | 72.4 | 4 | 768 | 102 | 766 | 102 | 781 | 99.8 |

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

General Notes

BIOS settings:

Snoop Filter: Disabled

Hardware Prefetcher: Disabled

Adjacent Sector Prefetch: Disabled

All benchmarks compiled in 64-bit mode except 437.leslie3d, 450.soplex

470.lbm and 482.sphinx3, at peak, are compiled in 32-bit mode

The taskset utility was used to bind processes to cores

Parallel settings for 436.cactusADM peak:

OMP_NUM_THREADS = 8

KMP_AFFINITY = physical,0

KMP_STACKSIZE = 64M



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

SGI

SGI Altix ICE 8200
(Intel Xeon E5440, 2.83 GHz)

SPECfp_rate2006 = 75.7

SPECfp_rate_base2006 = 68.1

CPU2006 license: 4
Test sponsor: SGI
Tested by: SGI

Test date: Jan-2007
Hardware Availability: Jan-2008
Software Availability: Nov-2007

Base Compiler Invocation

C benchmarks:
icc

C++ benchmarks:
icpc

Fortran benchmarks:
ifort

Benchmarks using both Fortran and C:
icc ifort

Base Portability Flags

410.bwaves: -DSPEC_CPU_LP64
416.gamess: -DSPEC_CPU_LP64
433.milc: -DSPEC_CPU_LP64
434.zeusmp: -DSPEC_CPU_LP64
435.gromacs: -DSPEC_CPU_LP64 -nofor_main
436.cactusADM: -DSPEC_CPU_LP64 -nofor_main
437.leslie3d: -DSPEC_CPU_LP64
444.namd: -DSPEC_CPU_LP64
447.dealII: -DSPEC_CPU_LP64
450.soplex: -DSPEC_CPU_LP64
453.povray: -DSPEC_CPU_LP64
454.calculix: -DSPEC_CPU_LP64 -nofor_main
459.GemsFDTD: -DSPEC_CPU_LP64
465.tonto: -DSPEC_CPU_LP64
470.lbm: -DSPEC_CPU_LP64
481.wrf: -DSPEC_CPU_LP64 -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LINUX
482.sphinx3: -DSPEC_CPU_LP64

Base Optimization Flags

C benchmarks:
-fast

C++ benchmarks:
-fast

Fortran benchmarks:
-fast

Benchmarks using both Fortran and C:
-fast



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

SGI

SGI Altix ICE 8200
(Intel Xeon E5440, 2.83 GHz)

SPECfp_rate2006 = 75.7

SPECfp_rate_base2006 = 68.1

CPU2006 license: 4

Test sponsor: SGI

Tested by: SGI

Test date: Jan-2007

Hardware Availability: Jan-2008

Software Availability: Nov-2007

Peak Compiler Invocation

C benchmarks (except as noted below):

```
/opt/intel/cc/10.1.008/bin/icc -L/opt/intel/cc/10.1.008/lib
-I/opt/intel/cc/10.1.008/include
```

433.milc: icc

C++ benchmarks (except as noted below):

icpc

```
450.soplex: /opt/intel/cc/10.1.008/bin/icpc -L/opt/intel/cc/10.1.008/lib
-I/opt/intel/cc/10.1.008/include
```

Fortran benchmarks (except as noted below):

ifort

```
437.leslie3d: /opt/intel/fc/10.1.008/bin/ifort -L/opt/intel/fc/10.1.008/lib
-I/opt/intel/fc/10.1.008/include
```

Benchmarks using both Fortran and C:

icc ifort

Peak Portability Flags

```
410.bwaves: -DSPEC_CPU_LP64
416.gamess: -DSPEC_CPU_LP64
433.milc: -DSPEC_CPU_LP64
434.zeusmp: -DSPEC_CPU_LP64
435.gromacs: -DSPEC_CPU_LP64 -nofor_main
436.cactusADM: -DSPEC_CPU_LP64 -nofor_main
444.namd: -DSPEC_CPU_LP64
447.deallI: -DSPEC_CPU_LP64
453.povray: -DSPEC_CPU_LP64
454.calculix: -DSPEC_CPU_LP64 -nofor_main
459.GemsFDTD: -DSPEC_CPU_LP64
465.tonto: -DSPEC_CPU_LP64
481.wrf: -DSPEC_CPU_LP64 -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LINUX
```

Peak Optimization Flags

C benchmarks:

```
433.milc: -prof-gen(pass 1) -prof-use(pass 2) -fast -fno-alias
-auto-ilp32
```

```
470.lbm: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2
-scalar-rep- -prefetch -opt-malloc-options=3
```

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

SGI

SGI Altix ICE 8200
(Intel Xeon E5440, 2.83 GHz)

SPECfp_rate2006 = 75.7

SPECfp_rate_base2006 = 68.1

CPU2006 license: 4
Test sponsor: SGI
Tested by: SGI

Test date: Jan-2007
Hardware Availability: Jan-2008
Software Availability: Nov-2007

Peak Optimization Flags (Continued)

482.sphinx3: -fast -unroll2

C++ benchmarks:

444.namd: -prof-gen(pass 1) -prof-use(pass 2) -fast -fno-alias
-auto-ilp32

447.dealIII: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2
-ansi-alias -scalar-rep-

450.soplex: -prof-gen(pass 1) -prof-use(pass 2) -fast
-opt-malloc-options=3

453.povray: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll4
-ansi-alias

Fortran benchmarks:

410.bwaves: -fast -prefetch

416.gamess: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2 -Ob0
-ansi-alias -scalar-rep-

434.zeusmp: -prof-gen(pass 1) -prof-use(pass 2) -fast

437.leslie3d: -prof-gen(pass 1) -prof-use(pass 2) -fast -prefetch
-opt-malloc-options=3

459.GemsFDTD: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2 -Ob0
-prefetch

465.tonto: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll4 -auto

Benchmarks using both Fortran and C:

435.gromacs: -prof-gen(pass 1) -prof-use(pass 2) -fast -prefetch
-auto-ilp32

436.cactusADM: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2
-prefetch -parallel -auto-ilp32

454.calculix: -fast -unroll-aggressive -auto-ilp32

481.wrf: -fast -auto-ilp32

The flags file that was used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Intel-ic10.1-FP-intel64-linux-flags.20090714.03.html>



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

SGI

SGI Altix ICE 8200
(Intel Xeon E5440, 2.83 GHz)

SPECfp_rate2006 = 75.7

SPECfp_rate_base2006 = 68.1

CPU2006 license: 4

Test sponsor: SGI

Tested by: SGI

Test date: Jan-2007

Hardware Availability: Jan-2008

Software Availability: Nov-2007

You can also download the XML flags source by saving the following link:

<http://www.spec.org/cpu2006/flags/Intel-ic10.1-FP-intel64-linux-flags.20090714.03.xml>

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.0.
Report generated on Tue Jul 22 16:34:12 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 6 February 2008.