



# SPEC® CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Intel Corporation

Intel Desktop Board DQ35JO (Intel Core 2 Duo Q9550)

**SPECint\_rate2006 = 68.0**

**SPECint\_rate\_base2006 = 61.0**

CPU2006 license: 13


Test sponsor: Intel Corporation

Tested by: Intel Corporation

Test date: Feb-2008

Hardware Availability: Mar-2008

Software Availability: Nov-2007



**SPECint\_rate\_base2006 = 61.0**

**SPECint\_rate2006 = 68.0**

### Hardware

CPU Name: Intel Core 2 Quad Q9550  
 CPU Characteristics: 2.83 GHz, 1333 FSB  
 CPU MHz: 2833  
 FPU: Integrated  
 CPU(s) enabled: 4 cores, 1 chip, 4 cores/chip  
 CPU(s) orderable: 1 chip  
 Primary Cache: 32 KB I + 32 KB D on chip per core  
 Secondary Cache: 12 MB I+D on chip per chip, 6 MB shared / 2 cores  
 L3 Cache: None  
 Other Cache: None  
 Memory: 4 GB (4x1GB Micron DDR2-800 CL5)  
 Disk Subsystem: Seagate 320GB NCQ SATA, 16MB cache, 7200 RPM  
 Other Hardware: None

### Software

Operating System: Windows Vista Ultimate (64-bit)  
 Compiler: Intel C++ Compiler for IA32 version 10.1  
 Build 20070913 Package ID: w\_cc\_p\_10.1.011  
 Microsoft Visual Studio 2005 SP1 (for libraries)  
 Auto Parallel: Yes  
 File System: NTFS  
 System State: Default  
 Base Pointers: 32-bit  
 Peak Pointers: 32-bit  
 Other Software: SmartHeap Library Version 8.1 from <http://www.microquill.com/>



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Intel Corporation

Intel Desktop Board DQ35JO (Intel Core 2 Duo Q9550)

**SPECint\_rate2006 = 68.0**

**SPECint\_rate\_base2006 = 61.0**

CPU2006 license: 13

Test date: Feb-2008

Test sponsor: Intel Corporation

Hardware Availability: Mar-2008

Tested by: Intel Corporation

Software Availability: Nov-2007

## Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	4	<b>581</b>	<b>67.3</b>	583	67.0	581	67.3	4	445	87.8	<b>445</b>	<b>87.8</b>	448	87.2
401.bzip2	4	<b>672</b>	<b>57.4</b>	670	57.6	675	57.2	4	650	59.4	658	58.6	<b>651</b>	<b>59.3</b>
403.gcc	4	582	55.3	589	54.7	<b>584</b>	<b>55.1</b>	4	<b>592</b>	<b>54.4</b>	579	55.6	599	53.8
429.mcf	4	574	63.5	574	63.6	<b>574</b>	<b>63.6</b>	4	<b>570</b>	<b>64.1</b>	569	64.1	570	64.0
445.gobmk	4	560	74.9	559	75.1	<b>559</b>	<b>75.0</b>	4	515	81.4	514	81.7	<b>514</b>	<b>81.6</b>
456.hammer	4	630	59.2	<b>630</b>	<b>59.2</b>	630	59.2	4	580	64.3	581	64.3	<b>581</b>	<b>64.3</b>
458.sjeng	4	720	67.2	720	67.2	<b>720</b>	<b>67.2</b>	4	638	75.8	<b>638</b>	<b>75.8</b>	639	75.8
462.libquantum	4	1692	49.0	1691	49.0	<b>1691</b>	<b>49.0</b>	1	243	85.1	<b>243</b>	<b>85.1</b>	246	84.3
464.h264ref	4	<b>755</b>	<b>117</b>	755	117	755	117	4	716	124	717	124	<b>717</b>	<b>124</b>
471.omnetpp	4	671	37.3	<b>670</b>	<b>37.3</b>	669	37.4	4	655	38.2	655	38.2	<b>655</b>	<b>38.2</b>
473.astar	4	<b>637</b>	<b>44.1</b>	639	44.0	637	44.1	4	<b>593</b>	<b>47.3</b>	593	47.3	596	47.1
483.xalancbmk	4	397	69.5	398	69.4	<b>397</b>	<b>69.4</b>	4	383	72.0	<b>383</b>	<b>72.0</b>	384	71.9

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

## General Notes

Tested systems can be used with Shin-G ATX case, Antec NeoPower 480W power supply Product description located as of 03/2008:

<http://www.intel.com/products/motherboard/DQ35JO/index.htm>

The system bus runs at 1333 MHz

System was configured with Asus EN8800GTX discrete graphics card

Binaries were built on Windows Vista Ultimate (32-bit)

The following VS 2005 SP1 updates were applied: KB926601 and KB932232

OMP\_NUM\_THREADS was set to number of logical processors as seen by the OS

KMP\_AFFINITY was set to physical,0

submit was disabled for 462.libquantum at peak.

## Base Compiler Invocation

C benchmarks:

  icl -Qvc8 -Qc99

C++ benchmarks:

  icl -Qvc8

## Base Portability Flags

403.gcc: -DSPEC\_CPU\_WIN32

464.h264ref: -DSPEC\_CPU\_NO\_INTTYPES -DWIN32

Continued on next page



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Intel Corporation

Intel Desktop Board DQ35JO (Intel Core 2 Duo Q9550)

**SPECint\_rate2006 = 68.0**

**SPECint\_rate\_base2006 = 61.0**

**CPU2006 license:** 13

**Test sponsor:** Intel Corporation

**Tested by:** Intel Corporation

**Test date:** Feb-2008

**Hardware Availability:** Mar-2008

**Software Availability:** Nov-2007

## Base Portability Flags (Continued)

483.xalancbmk: -Qoption\_cpp, --no\_wchar\_t\_keyword

## Base Optimization Flags

C benchmarks:

-fast -Qvec-guard-write /F512000000

C++ benchmarks:

-fast -Qcxx\_features /F512000000 shlw32m.lib  
-link /FORCE:MULTIPLE

## Base Other Flags

C benchmarks:

403.gcc: -Dalloca=\_alloca

## Peak Compiler Invocation

C benchmarks:

icl -Qvc8 -Qc99

C++ benchmarks:

icl -Qvc8

## Peak Portability Flags

403.gcc: -DSPEC\_CPU\_WIN32

464.h264ref: -DSPEC\_CPU\_NO\_INTTYPES -DWIN32

483.xalancbmk: -Qoption\_cpp, --no\_wchar\_t\_keyword

## Peak Optimization Flags

C benchmarks:

400.perlbench: -Qprof\_gen(pass 1) -Qprof\_use(pass 2) -fast -Qansi-alias  
-Qprefetch /F512000000 shlw32m.lib  
-link /FORCE:MULTIPLE

Continued on next page



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Intel Corporation

Intel Desktop Board DQ35JO (Intel Core 2 Duo Q9550)

**SPECint\_rate2006 = 68.0**

**SPECint\_rate\_base2006 = 61.0**

**CPU2006 license:** 13

**Test date:** Feb-2008

**Test sponsor:** Intel Corporation

**Hardware Availability:** Mar-2008

**Tested by:** Intel Corporation

**Software Availability:** Nov-2007

## Peak Optimization Flags (Continued)

401.bzip2: -Qprof\_gen(pass 1) -Qprof\_use(pass 2) -fast -Qprefetch  
/F512000000

403.gcc: -Qprof\_gen(pass 1) -Qprof\_use(pass 2) -fast /F512000000

429.mcf: -Qprof\_gen(pass 1) -Qprof\_use(pass 2) -fast -Qprefetch  
/F512000000 shlw32m.lib -link /FORCE:MULTIPLE

445.gobmk: -Qprof\_gen(pass 1) -Qprof\_use(pass 2) -QxT -O2 -Qipo  
-Qprec-div- -Qansi-alias /F512000000

456.hmmr: -Qprof\_gen(pass 1) -Qprof\_use(pass 2) -fast -Qunroll2  
-Qansi-alias -Qopt-multi-version-aggressive /F512000000

458.sjeng: -Qprof\_gen(pass 1) -Qprof\_use(pass 2) -fast -Qunroll4  
/F512000000

462.libquantum: -fast -Qunroll14 -Ob0 -Qprefetch  
-Qopt-streaming-stores:always -Qparallel  
-Qpar-runtime-control /F512000000

464.h264ref: -Qprof\_gen(pass 1) -Qprof\_use(pass 2) -fast -Qunroll2  
-Qansi-alias /F512000000

C++ benchmarks:

471.omnetpp: -Qprof\_gen(pass 1) -Qprof\_use(pass 2) -fast -Qansi-alias  
-Qopt-ra-region-strategy=block -Qcxx\_features /F512000000  
shlw32m.lib -link /FORCE:MULTIPLE

473.astar: -Qprof\_gen(pass 1) -Qprof\_use(pass 2) -fast -Qansi-alias  
-Qopt-ra-region-strategy=routine -Qcxx\_features /F512000000  
shlw32m.lib -link /FORCE:MULTIPLE

483.xalancbmk: -Qprof\_gen(pass 1) -Qprof\_use(pass 2) -fast -Qansi-alias  
-Qcxx\_features /F512000000 shlw32m.lib  
-link /FORCE:MULTIPLE

## Peak Other Flags

C benchmarks:

403.gcc: -Dalloca=\_alloca

The flags file that was used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Intel-ic10.1-win32-flags.html>



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Intel Corporation

Intel Desktop Board DQ35JO (Intel Core 2 Duo Q9550)

**SPECint\_rate2006 = 68.0**

**SPECint\_rate\_base2006 = 61.0**

**CPU2006 license:** 13

**Test date:** Feb-2008

**Test sponsor:** Intel Corporation

**Hardware Availability:** Mar-2008

**Tested by:** Intel Corporation

**Software Availability:** Nov-2007

You can also download the XML flags source by saving the following link:

<http://www.spec.org/cpu2006/flags/Intel-ic10.1-win32-flags.xml>

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.  
For other inquiries, please contact [webmaster@spec.org](mailto:webmaster@spec.org).

Tested with SPEC CPU2006 v1.0.

Report generated on Tue Jul 22 15:25:07 2014 by SPEC CPU2006 PS/PDF formatter v6932.

Originally published on 19 March 2008.