



STORMSHIELD

NETWORK SECURITY

STORMSHIELD SN-XL-SERIES-6200

Stormshield's most powerful firewall

318 Gbps

FIREWALL
PERFORMANCE

64 Gbps

IPSEC VPN
PERFORMANCE

11 Gbps

ANTIVIRUS
PERFORMANCE

Modularity

NEXT-GENERATION COPPER
AND FIBRE INTERFACES



Very high performance

The SN-XL-Series-6200's 318 Gbps Firewall throughput meets the high throughput needs of today's and tomorrow's critical infrastructures.



Modularity

- Very high density of fibre ports
- Next-generation network interface modules enabling interfaces up to 100Gb



Peace of mind

- IPMI (Intelligent Platform Management Interface)
- RAID 1 configuration with hot-swappable disks
- Redundant power supply and ventilation for continuity of service



All-in-one equipment

- High-performance Secure SD-WAN concentrator
- IPsec VPN and intrusion prevention
- Interactive reports to facilitate risk mitigation



NEXT GENERATION UTM
& FIREWALL

LARGE ORGANISATIONS
& DATACENTERS

WWW.STORMSHIELD.COM

TECHNICAL SPECIFICATIONS

PERFORMANCE*

Firewall throughput (UDP 1518 bytes)	318 Gbps
Firewall throughput (IMIX**)	72 Gbps
IPS throughput (UDP 1518 bytes)	132 Gbps
IPS throughput (1 MB HTTP)	40 Gbps
Antivirus throughput	11 Gbps

VPN

IPSec throughput - AES-GCM***	64 Gbps
IPSec throughput - AES-GCM (IMIX)***	29 Gbps
Max. number of IPSec VPN tunnels	30000
Number of simultaneous SSL VPN clients	7500

NETWORK CONNECTIVITY

Max. number of simultaneous sessions	25000000
Number of new sessions/sec.	335000
(Max.) number of main / backup gateways	64/64

CONNECTIVITY

Copper 10/100/1000/2500 interfaces	2-64
10 Gb copper interfaces	0-32
1 Gb fibre interfaces	0-62
10 Gb fibre interfaces (Dual speed)	0-32
40 Gb fibre interfaces	0-16
Optional network extension modules (8 x 10/100/1000/2500 copper ports - 4 x 10 Gb copper ports - 8 x 1 Gb fibre ports - 4 x 10 Gb fibre ports - 2 x 40 Gb fibre ports)	8

SYSTEM

Number of filtering rules (recommended / specific conf.)	16,384 / 32,768
Maximum number of static routes	10240

REDUNDANCY

High availability (Active/Passive)	✓
Redundant SSDs (hot swappable)	RAID 1
Redundant power supply (hot swappable)	✓
Redundant ventilation (hot swappable)	✓

HARDWARE

Storage	480 Gb SSD
Large Storage option for local storage	960 Gb SSD
MTBF at 25°C (in years)	22.9
Size	2U - 19"
Height x Width x Depth (mm)	88.9 x 443 x 650
Weight	18.97kg (41.82 lbs)
Power supply (AC)	2 x 100 240V 60-50Hz 13-10A
48V power supply (option)	2 x -40-72VDC 50A MAX
Power consumption (max)	230V 50Hz 559.65W 2.46A
Fans	5
Heat dissipation (max., BTU/h)	2300
Operating temperature	0° to 40°C (32° to 104°F)
Operating relative humidity (non-condensing)	0% to 95% @ 40°C (104°F)
Storage temperature	-30° to 65°C (-22° to 149°F)
Storage relative humidity (non-condensing)	5% to 95% @ 60°C (140°F)

CERTIFICATIONS

Compliance	CE/FCC/RCM/UKCA/CB
------------	--------------------

The images in this document are not contractually binding.

FEATURES

CONTROL OF USE

Firewall/IPS/IDS mode - User identity-based firewall - Application detection and management - Microsoft Services Firewall - Industrial firewall/IPS/IDS - Industrial application control - Mobile device usage detection and control - Application inventory (optional) - Vulnerability detection (optional) - Geolocation (countries, continents) - Dynamic machine reputation - URL filtering (embedded or cloud mode) - Transparent authentication (Active Directory SSO Agent, SSL, SPNEGO) - VDI multi-user authentication with agent (Citrix-TSE) - Guest or sponsor mode authentication, webservices.

PROTECTION AGAINST THREATS

Intrusion detection and prevention - Auto-detection and protocol compliance checking - Application inspection - Denial of Service (DoS) protection - SQL injection protection - Cross Site Scripting (XSS) protection - Malicious code and Web2.0 scripts protection - Trojan horse detection - Interactive connection detection (Botnet, Command&Control) - Evasion techniques protection - Advanced fragmentation management - Automated quarantine in case of attack - Antispam and antiphishing: Reputation analysis, heuristic engine - Integrated antivirus software (HTTP, SMTP, POP3, FTP) - SSL decryption and inspection - VoIP (SIP) protection - Collaborative security: IP reputation, Sandbox Cloud hosted in Europe (optional).

CONFIDENTIALITY OF EXCHANGES

Site-to-site or nomadic IPSec VPN - SSL VPN remote access in multiple OS tunnel mode (Windows, Android, iOS, etc.) - SSL VPN agent with automated configuration (Windows) - IPSec VPN support for Android/iPhone.

NETWORK - INTEGRATION

IPv6 - NAT, PAT, bridge/routed/hybrid mode - Dynamic routing (RIP, OSPF, BGP) - Multicast - Multiple link management (split, switch) - Multiple level internal or external PKI management - Multiple domain directories (including internal LDAP) - Explicit proxy - Policy-based routing (PBR) - Service quality management - DHCP client/relay/server - NTP client - DNS proxy-cache - HTTP proxy - LACP management - Spanning-tree management (RSTP/MSTP) - SD-WAN, Multiple factor authentication (MFA).

MANAGEMENT

Web-based management interface with privacy mode (GDPR compliant) - Object-oriented security policy - Contextual security policy - Real-time configuration assistance - Firewall rule usage counters - Online or offline security updates - Global/local security policy - Embedded reporting and log analysis tools - Interactive and customisable reports - Support for multiple UDP/TCP/TLS syslog servers - SNMP v1, v2, v3 agent - IPFIX - Automated configuration backup - Open API - Script recording.

.....
Non-binding document. The features mentioned are those of version 4.x.

* Performance measured in the laboratory under ideal conditions for version 4.8. The results may vary depending on the test conditions and the software version.

** IP size: 60% (48 bytes) - 25% (494 bytes) - 15% (1500 bytes).

*** Measures to be adjusted according to the future version.